

AXK - K

As09 1E ↔ F069 2E



Refrigerant
R410A | GWP=2.088



Centrifugal
fan



"Comfort"
Solution

Direct expansion with water cooled condenser



Configuration

- O - Upflow
- U - Downflow

Operation

- SF - Cooling only
- PC - Heat pump (available on request)

Solution

- K - Comfort

Cooling Capacity 9,5 - 95,7 kW

Housing	Base and panelling made of galvanised steel painted with epoxy powder; frame complete with service panels designed to grant proper operation during maintenance. The aesthetic panelling is internally lined to reduce the noise level.
Air heat exchanger	Air heat exchanger made of copper tubes arranged in staggered rows. The fins are made of aluminum with a special hydrophilic treatment for better drainage of the condensate and therefore better heat exchange.
Compressor	HERMETIC SCROLL type, complete with thermal protection. Antivibration mountings and oil charge are standard.
Fan	Centrifugal type with two suctions, directly coupled to the motor which is of external rotor type and is fixed by vibration isolation mountings. The fans have forward curved blades.
Water cooled condenser	High efficiency plate heat exchanger made of AISI 316 stainless steel.
Refrigerant circuit	Filter dryer, moisture-liquid sight glass, HP and LP pressure switches, solenoid valve, thermostatic expansion valve with external equalizer.
Filter	Folded type, mounted on a frame, with protection grille. Filtering cells in polyester fibers. G4 efficiency according to CEN-EN 779 norm; with 90,1% ASHRAE separation degree. The filter is of selfextinguish type.
Electrical board	It is designed and wired according to IEC 204-1/EN60204-1 regulations, complete with contactor and protection for compressors and fans, main isolator.
Control panel	The microprocessor controls the unit capacity by timing the compressors and checks the operating alarms. Advanced electronic control is standard.

ACCESSORIES

- Water heating coil
- Electric heating coil
- Electronic expansion valve
- Contacts for smoke/fire alarm
- F5 efficiency air folded filter
- Special filter plenum for air outlet (from F6 to F9)
- Air supply plenum with two directions adjustable grilles
- Max and min voltage relay
- Phase sequence relay
- Crankcase electrical heater
- Clock board
- LonWorks® and ModBus® interface electronic board
- Water on the bottom alarm
- Dirty filters alarm
- Low air flow alarm
- Non return air damper
- Vibration isolation frame with bearings (H 285-400mm.)
- Remote control panel
- Modulating humidifier (water conductivity 350...750 µS/cm)
- Condensing pressure valve
- Sound absorber plenum
- Shell and tube Condenser
- CU/NI Shell and tube Condenser

AXK - K

As09 1E ↔ F069 2E

Direct expansion with water cooled condenser

AXK Comfort		As09 1E	As12 1E	A017 1E	A020 1E	Bs21 1E	Bs23 1E	Bs25 1E	B028 1E	B030 1E
Total cooling capacity(1)	kW	9,5	12,1	17,1	20,0	20,7	23,1	25,3	27,8	30,0
Sensible cooling capacity(1)	kW	7,9	8,9	13,4	14,6	16,8	17,8	18,7	22,6	23,5
Power supply	-	400V/3+N/50Hz +T								
Number of compressors	n°	1	1	1	1	1	1	1	1	1
Number of refrigerant circuits	n°	1	1	1	1	1	1	1	1	1
Compressors total power input(1)	kW	1,6	2,2	2,6	3,4	3,5	3,9	4,4	4,5	4,9
Compressors total current(1)	A	3,1	4,4	5,4	7,1	7,2	7,3	9,1	9,2	11,1
Air flow	m3/h	2300	2300	3300	3300	4200	4200	4200	5600	5600
External static pressure	Pa	80	80	80	80	150	150	150	125	125
Fans quantity	n°	1	1	1	1	1	1	1	2	2
Fans power input	kW	0,35	0,35	0,55	0,55	0,75	0,75	0,75	1,5	1,5
Fans total current	A	3,1	3,1	4,6	4,6	3,1	3,1	3,1	6,2	6,2
Front sound pressure OVER(2)	dB(A)	52	52	53	53	53	53	53	56	56
Front sound pressure UNDER(2)	dB(A)	49	49	50	50	50	50	50	53	53
IN-OUT diameter cond. water (CITY)	"	¾"	¾"	¾"	¾"	¾"	¾"	¾"	¾"	¾"
IN-OUT diameter cond. water (TOWER)	"	1"	1"	1¼"	1¼"	1¼"	1¼"	1¼"	1¼"	1¼"

ELECTRIC COIL										
Stages of operation	n°	1	1	2	2	2	2	2	2	2
Power	kW	3,0	3,0	6,0	6,0	6,0	6,0	6,0	6,0	6,0
Absorbed current	A	4,4	4,4	8,7	8,7	8,7	8,7	8,7	8,7	8,7

HUMIDIFIER										
Capacity	kg/h	1 - 3	1 - 3	1 - 3	1 - 3	1 - 3	1 - 3	1 - 3	5 - 8	5 - 8
Power	kW	2,3	2,3	2,3	2,3	2,3	2,3	2,3	6,2	6,2
Absorbed current	A	3,2	3,2	3,2	3,2	3,2	3,2	3,2	8,7	8,7

DIMENSIONS AND WEIGHT										
Lenght	mm	700	700	880	880	880	880	880	1140	1140
Depth	mm	700	700	700	700	700	700	700	700	700
Height	mm	1950	1950	1950	1950	1950	1950	1950	1950	1950
Operating weight	Kg	215	225	250	260	260	270	280	340	350

AXK Comfort		B034 1E	C039 1E	C045 1E	D054 2E	D058 2E	D066 2E	E079 2E	F083 2E	F096 2E
Total cooling capacity(1)	kW	34,1	39,1	45,1	53,7	58,1	65,6	79,2	82,5	95,7
Sensible cooling capacity(1)	kW	25,1	30,3	32,8	42,7	44,4	47,5	59,8	65,6	70,8
Power supply	-	400V/3+N/50Hz +T								
Number of compressors	n°	1	1	1	2	2	2	2	2	2
Number of refrigerant circuits	n°	1	1	1	2	2	2	2	2	2
Compressors total power input(1)	kW	5,9	6,7	8,6	9,1	11,1	13,2	13,6	13,7	15,7
Compressors total current(1)	A	13,2	13,6	15,7	18,2	22,2	26,4	27,2	27,4	31,4
Air flow	m3/h	5600	8200	8200	10500	10500	10500	14000	14000	16000
External static pressure	Pa	125	125	125	155	155	155	140	140	140
Fans quantity	n°	2	2	2	3	3	3	4	4	4
Fans power input	kW	1,5	1,5	1,5	2,25	2,25	2,25	3,0	3,0	3,0
Fans total current	A	6,2	6,2	6,2	9,3	9,3	9,3	12,4	12,4	12,4
Front sound pressure OVER(2)	dB(A)	56	56	56	60	60	60	61	62	62
Front sound pressure UNDER(2)	dB(A)	53	53	53	57	57	57	58	59	59
IN-OUT diameter cond. water (CITY)	"	¾"	1"	1"	1"	1"	1"	1¼"	1¼"	1¼"
IN-OUT diameter cond. water (TOWER)	"	1¼"	1½"	1½"	2"	2"	2"	2"	2"	2½"

ELECTRIC COIL										
Stages of operation	n°	2	2	2	2	2	2	2	2	2
Power	kW	6,0	9,0	9,0	12,0	12,0	12,0	18,0	18,0	18,0
Absorbed current	A	8,7	13,0	13,0	17,4	17,4	17,4	26,0	26,0	26,0

HUMIDIFIER										
Capacity	kg/h	5 - 8	5 - 8	5 - 8	5 - 8	5 - 8	5 - 8	10 - 15	10 - 15	10 - 15
Power	kW	6,2	6,2	6,2	6,2	6,2	6,2	11,3	11,3	11,3
Absorbed current	A	8,7	8,7	8,7	8,7	8,7	8,7	16,2	16,2	16,2

DIMENSIONS AND WEIGHT										
Lenght	mm	1140	1320	1320	1760	1760	1760	2200	2640	2640
Depth	mm	700	840	840	840	840	840	840	840	840
Height	mm	1950	1950	1950	1950	1950	1950	1950	1950	1950
Operating weight	Kg	360	440	450	530	540	550	750	960	980

Note:

- (1) Air inlet 26.7°C / 50% U.r. IN-OUT water condenser temperature = 30°C / 35°C
 - (2) Data measured at 1m in open field conditions
- THE DECLARED COOLING CAPACITY ARE NOT TAKING INTO ACCOUNT THE FAN MOTOR POWER INPUT.