

HERA BS

R290
Refrigerant
R290 | GWP=3

Reversible
heat pump

Inverter

Axial fan

Semi-hermetic
piston compresso

Brazed plate
heat exchanger

200-2-2 PV ↔ 720-4-4 PV

SCOP

Air-To-Water heat pump for low and medium temperatures applications



Solution

B - Base
P - Base with Pump

Version

LN - Low Noise
SL - Super Low Noise
XL - Extra Low Noise

Equipment

AS - Standard equipment
DS - Desuperheater

Heating capacity 197 - 710 kW
Cooling capacity 182 - 630 kW

Safety system	To ensure high-safety-level the unit is equipped with an ATEX certified gas detector and an EC centrifugal extraction fan. The sensor, with external dedicated power supply and Modbus output signal, has an alarm threshold set at 10% of the lower flammable limit (LFL). The Propane alarm causes the immediate shutdown of the machine and the centrifugal extraction fan is switched on, which allows the ventilation of the compressor compartment and the dilution of the R290 concentration to values below the lower flammability limit.
Structure	Structure specifically designed for outdoor installation. Basement and frame in galvanised shaped sheet steel with a suitable thickness. All parts are polyester-powder painted to assure total weather resistance (RAL 7035 standard colour, others on request). LN (Low Noise) version: the panels are internally lined with sound-absorbing material. SL (Super Low Noise) version: the panels are sandwich and insulated with rock wool. XL (Extra Low Noise) version: the panels are sandwich and insulated with rock wool and silenced fans with bionic shaped blades.
Compressor with inverter	Reciprocating semi-hermetic type, fixed on anti-vibration system and complete with pressure lubrication system, oil crankcase heater, integral electronic protection, valves and flexible joints on suction and discharge. A VFD (Variable Frequency Drive) is provided in order to adapt the capacity of the reciprocating compressor to the demand. The compressor is mechanically optimized for use with Hydrocarbons.
EC Fan	Premium-Axial-Fans with an high-efficient EC (Electronically Commutated) external rotor motors, sealed in protection IP54 and thermal class THCL 155. The motor efficiency class complies with IE4.
Source heat exchanger	Finned coil made with copper pipes arranged on staggered rows, mechanically expanded inside a pack of aluminium fins offering a high exchange surface area.
User heat exchanger	Brazed plate-type heat exchanger, stainless steel AISI 316 made, complete with water differential pressure switch, air vent valve and thermally insulated with closed-cell neoprene anti-condensate material. The heat exchanger design provides high thermal exchange and high performance results, furthermore it guarantees small dimensions and easy installation and maintenance.
Electrical board	Each unit is equipped with electric panel, built, wired and fully tested at the factory. Wiring numeration and optimized layout facilitate troubleshooting. The installed components are identified by nameplates to better identify the application and the type of action. Switchboard is made according to standards IEC 204-1/EN60204-1 and it is complete with the following main components: - Main isolator switch - Door interlock safety device - Contactor and protection for compressor and fans - Cabinet minimum protection rating IP54.
Control	The microprocessor controls the unit capacity by timing the compressors and checks the operating alarms with the possibility to connect to BMS.
Refrigerant circuit	Filter drier, moisture-liquid sight glass, electronic expansion valve, high & low pressure gauge, high and low pressure transducers, high pressure switch and safety high pressure valve.

MAIN ACCESSORIES

- Anti-vibration rubber/spring mounts
- Low pressure switch
- Low pressure safety valve
- Double safety valve
- Finned pack heat exchanger Copper/Copper
- Overpressure valve / automatic by-pass
- Double water pump (stand-by) - Standard/ High pressure
- Water filter
- Double gas detector with separate electrical supply

HERA BS

Technical data

HERA BS R290		200-2-2 PV	240-2-2 PV	305-2-2 PV	335-2-2 PV	380-2-2 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	201	239	297	333	377
Total power input ⁽¹⁾	[kW]	69,9	84,1	96,2	108,0	126
COP	[-]	2,88	2,84	3,09	3,08	2,99
Heating Capacity⁽¹⁾ (XL versions)	[kW]	197	236	293	329	375
Total power input ⁽¹⁾	[kW]	68,8	82,9	95,2	106,0	125
COP	[-]	2,86	2,85	3,08	3,10	3,00
Water flow ⁽¹⁾	[m ³ /h]	34,9	41,5	51,5	57,8	65,4
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	49,9	59,3	52,1	46,4	50,5
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	33,2 / 41,9	39,4 / 49,8	48,9 / 61,8	54,9 / 69,4	62,1 / 78,5
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate						
SCOP (LN/SL - XL)	[W/W]	3,417 - 3,443	3,384 - 3,386	3,512 - 3,558	3,535 - 3,344	3,201 - 3,234
$\eta_{s,h}$ (LN/SL - XL)	[%]	133,7 - 134,7	132,3 - 132,5	137,5 - 139,3	138,4 - 130,8	125 - 126,4
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate						
SCOP (LN/SL - XL)	[W/W]	3,053 - 2,849	2,824 - 2,83	2,976 - 3,011	2,996 - 3,032	2,928 - 2,939
$\eta_{s,h}$ (LN/SL - XL)	[%]	119,1 - 111	110 - 110,2	116,1 - 117,4	116,9 - 118,3	114,1 - 114,5
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	183	214	260	290	326
Total power input ⁽²⁾	[kW]	75,1	90,4	106	118	137
EER	[-]	2,44	2,37	2,45	2,46	2,38
Cooling Capacity⁽²⁾ (XL versions)	[kW]	182	214	258	291	324
Total power input ⁽²⁾	[kW]	73,8	89,5	102	115	134
EER	[-]	2,47	2,39	2,53	2,53	2,42
Water flow ⁽²⁾	[m ³ /h]	31,4	36,8	44,7	49,9	56,0
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	43,5	50,1	43,2	40,8	40,9
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	25,1 / 37,7	29,4 / 44,2	35,8 / 53,6	39,9 / 59,9	44,8 / 67,2
Technical data						
Refrigerant / GWP	-	R290 / 3				
Charge of refrigerant	[Kg]	> 12				
Number of refrigerant circuits	N°	2				
Compressor type / quantity	-/N°	Semihhermetic reciprocating with VFD (Variable Frequency Drive) / 2				
Expansion valve type	-	Electronic				
Fans quantity / type	-	4 / Axial EC		8 / Axial EC		
Fans power input ⁽¹⁾ (total)	[kW]	1,54	1,67	2,28	2,45	2,62
Total air flow ⁽¹⁾	[m ³ /h]	50.050	51.600	89.800	92.150	94.400
Electrical data						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum absorbed power	[kW]	87,9	97,9	138	141	151
Locked rotor current - LRA	[A]	153	168	238	245	261
Maximum absorbed current (full load)	[A]	153	168	238	245	261
Solution BASE-P - with Hydronic Kit						
Pump type	-	Centrifugal				
Standard pump (1,5 bar)						
Motor efficiency	-	IE3				
Pump motor nominal power input	[kW]	3,0	3,0	4,0	5,5	5,5
Pump motor nominal absorbed current	[A]	6,4	6,4	8,7	10,6	10,6
Increased pump (3,0 bar)						
Motor efficiency	-	IE3				
Pump motor nominal power input	[kW]	5,5	7,5	7,5	9,2	9,2
Pump motor nominal absorbed current	[A]	10,6	13,6	13,6	17,2	17,2
Water connections						
Size (nominal external diameter)	[inch]	3" (DN 80)	3" (DN 80)	4" (DN 100)	4" (DN 100)	4" (DN 100)
Noise levels⁽³⁾						
Total sound power (LN version)	[db(A)]	86	87	91	92	93
Total sound pressure (LN version) - at 1 m distance	[db(A)]	67	68	71	72	73
Total sound pressure (LN version) - at 10 m distance	[db(A)]	54	55	59	60	61
Total sound power (SL version)	[db(A)]	85	86	90	91	92
Total sound pressure (SL version) - at 1 m distance	[db(A)]	66	67	70	71	72
Total sound pressure (SL version) - at 10 m distance	[db(A)]	53	54	58	59	60
Total sound power (XL version)	[db(A)]	83	84	88	89	90
Total sound pressure (XL version) - at 1 m distance	[db(A)]	64	65	68	69	70
Total sound pressure (XL version) - at 10 m distance	[db(A)]	51	52	56	57	58
Dimensions and weights - unit						
Length	[mm]	3.665	3.665	5.230	5.230	5.230
Width	[mm]	2.280	2.280	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	2.800	2.840	3.970	3.990	4.180
Shipment weight - BP/SL/AS/EC/II version	[Kg]	2.900	2.940	4.070	4.090	4.280
Shipment weight - BP/XL/AS/EC/II version	[Kg]	2.930	2.970	4.130	4.150	4.340

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202.

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202.

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA BS

Technical data

HERA BS R290		455-3-3 PV	500-3-3 PV	535-3-3 PV	565-3-3 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	446	499	533	566
Total power input ⁽¹⁾	[kW]	144	162	172	189
COP	[-]	3,10	3,08	3,10	2,99
Heating Capacity⁽¹⁾ (XL versions)	[kW]	445	492	528	562
Total power input ⁽¹⁾	[kW]	142	160	171	188
COP	[-]	3,13	3,08	3,09	2,99
Water flow ⁽¹⁾	[m ³ /h]	77,3	86,5	92,4	98,2
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	66,7	75,3	67,8	72,9
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	73,4 / 92,8	82,2 / 104	87,8 / 111	93,3 / 118
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate					
SCOP (LN/SL - XL)	[W/W]	3,558 - 3,617	3,515 - 3,371	3,375 - 3,407	3,203 - 3,25
$\eta_{s,h}$ (LN/SL - XL)	[%]	139,3 - 141,7	137,6 - 131,8	132 - 133,3	125,1 - 127
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate					
SCOP (LN/SL - XL)	[W/W]	2,986 - 3,03	3,001 - 3,022	3,03 - 3,055	2,93 - 2,94
$\eta_{s,h}$ (LN/SL - XL)	[%]	116,5 - 118,2	117 - 117,9	118,2 - 119,2	114,2 - 114,6
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	391	434	467	486
Total power input ⁽²⁾	[kW]	159	176	189	205
EER	[-]	2,46	2,47	2,47	2,49
Cooling Capacity⁽²⁾ (XL versions)	[kW]	389	430	467	484
Total power input ⁽²⁾	[kW]	154	171	185	200
EER	[-]	2,53	2,51	2,52	2,42
Water flow ⁽²⁾	[m ³ /h]	67,2	74,6	80,3	83,6
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	53,5	59,8	54,5	56,5
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	53,8 / 80,6	59,7 / 89,5	64,2 / 96,4	66,9 / 100
Technical data					
Refrigerant / GWP	-	R290 / 3			
Charge of refrigerant	[Kg]	> 12			
Number of refrigerant circuits	N°	3			
Compressor type / quantity	-/N°	Semihermetic reciprocating with VFD (Variable Frequency Drive) / 3			
Expansion valve type	-	Electronic			
Fans quantity / type	-	12 / Axial EC			
Fans power input ⁽¹⁾ (total)	[kW]	3,43	3,68	3,89	3,93
Total air flow ⁽¹⁾	[m ³ /h]	134.800	138.300	141.100	141.700
Electrical data					
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50			
Maximum absorbed power	[kW]	207	211	217	227
Locked rotor current - LRA	[A]	357	368	381	391
Maximum absorbed current (full load)	[A]	357	368	381	391
Solution BASE-P - with Hydronic Kit					
Pump type	-	Centrifugal			
Standard pump (1,5 bar)					
Motor efficiency	-	IE3			
Pump motor nominal power input	[kW]	5,5	5,5	7,5	7,5
Pump motor nominal absorbed current	[A]	10,6	10,6	13,6	13,6
Increased pump (3,0 bar)					
Motor efficiency	-	IE3			
Pump motor nominal power input	[kW]	9,2	11,0	11,0	11,0
Pump motor nominal absorbed current	[A]	17,2	21,3	21,3	21,3
Water connections					
Size (nominal external diameter)	[inch]	5" (DN 125)	5" (DN 125)	5" (DN 125)	6" (DN 150)
Noise levels⁽³⁾					
Total sound power (LN version)	[db(A)]	93	93	93	95
Total sound pressure (LN version) - at 1 m distance	[db(A)]	72	72	72	74
Total sound pressure (LN version) - at 10 m distance	[db(A)]	60	60	60	62
Total sound power (SL version)	[db(A)]	92	92	92	94
Total sound pressure (SL version) - at 1 m distance	[db(A)]	71	71	71	73
Total sound pressure (SL version) - at 10 m distance	[db(A)]	59	59	59	61
Total sound power (XL version)	[db(A)]	90	90	90	92
Total sound pressure (XL version) - at 1 m distance	[db(A)]	69	69	69	71
Total sound pressure (XL version) - at 10 m distance	[db(A)]	57	57	57	59
Dimensions and weights - unit					
Length	[mm]	7.475	7.475	7.475	7.475
Width	[mm]	2.280	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	5.960	5.960	6.250	6.290
Shipment weight - BP/SL/AS/EC/II version	[Kg]	6.060	6.060	6.350	6.390
Shipment weight - BP/XL/AS/EC/II version	[Kg]	6.150	6.150	6.440	6.480

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202:

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202:

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA BS

Technical data

HERA BS R290		665-4-4 PV	720-4-4 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	666	710
Total power input ⁽¹⁾	[kW]	215	230
COP	[-]	3,10	3,09
Heating Capacity⁽¹⁾ (XL versions)	[kW]	658	670
Total power input ⁽¹⁾	[kW]	213	229
COP	[-]	3,09	2,93
Water flow ⁽¹⁾	[m ³ /h]	116	123
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	50,9	50,2
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	110 / 139	117 / 148
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate			
SCOP (LN/SL - XL)	[W/W]	3,576 - 3,374	3,396 - 3,429
$\eta_{s,h}$ (LN/SL - XL)	[%]	140 - 132	132,8 - 134,2
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate			
SCOP (LN/SL - XL)	[W/W]	3,029 - 3,064	3,057 - 3,081
$\eta_{s,h}$ (LN/SL - XL)	[%]	118,2 - 119,6	119,3 - 120,3
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	581	630
Total power input ⁽²⁾	[kW]	235	253
EER	[-]	2,47	2,49
Cooling Capacity⁽²⁾ (XL versions)	[kW]	581	624
Total power input ⁽²⁾	[kW]	229	247
EER	[-]	2,54	2,53
Water flow ⁽²⁾	[m ³ /h]	99,9	108
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	44,3	42,4
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	79,9 / 120	86,4 / 130
Technical data			
Refrigerant / GWP	-	R290 / 3	
Charge of refrigerant	[Kg]	> 12	
Number of refrigerant circuits	N°	4	
Compressor type / quantity	-/N°	Semihermetic reciprocating with VFD (Variable Frequency Drive) / 4	
Expansion valve type	-	Electronic	
Fans quantity / type	-	16 / Axial EC	
Fans power input ⁽¹⁾ (total)	[kW]	4,90	5,17
Total air flow ⁽¹⁾	[m ³ /h]	184.300	187.900
Electrical data			
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50	
Maximum absorbed power	[kW]	281	289
Locked rotor current - LRA	[A]	490	508
Maximum absorbed current (full load)	[A]	490	508
Solution BASE-P - with Hydronic Kit			
Pump type	-	Centrifugal	
Standard pump (1,5 bar)			
Motor efficiency	-	IE3	
Pump motor nominal power input	[kW]	11	11
Pump motor nominal absorbed current	[A]	21,3	21,3
Increased pump (3,0 bar)			
Motor efficiency	-	IE3	
Pump motor nominal power input	[kW]	15,0	15,0
Pump motor nominal absorbed current	[A]	27,7	27,7
Water connections			
Size (nominal external diameter)	[inch]	6" (DN 150)	6" (DN 150)
Noise levels⁽³⁾			
Total sound power (LN version)	[db(A)]	95	96
Total sound pressure (LN version) - at 1 m distance	[db(A)]	74	74
Total sound pressure (LN version) - at 10 m distance	[db(A)]	62	63
Total sound power (SL version)	[db(A)]	94	95
Total sound pressure (SL version) - at 1 m distance	[db(A)]	73	73
Total sound pressure (SL version) - at 10 m distance	[db(A)]	61	62
Total sound power (XL version)	[db(A)]	92	93
Total sound pressure (XL version) - at 1 m distance	[db(A)]	71	71
Total sound pressure (XL version) - at 10 m distance	[db(A)]	59	60
Dimensions and weights - unit			
Length	[mm]	9.615	9.615
Width	[mm]	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550
Height (XL)	[mm]	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	7.880	8.340
Shipment weight - BP/SL/AS/EC/II version	[Kg]	7.980	8.440
Shipment weight - BP/XL/AS/EC/II version	[Kg]	8.100	8.560

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202.

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202.

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA HE

R290
Refrigerant
R290 | GWP=3

Reversible
heat pump

Inverter

Axial fan

Semi-hermetic
piston compresso

Brazed plate
heat exchanger

195-2-2 PV ↔ 710-4-4 PV



High efficiency Air-To-Water heat pump for low and medium temperatures applications



Solution

B - Base
P - Base with Pump

Version

LN - Low Noise
SL - Super Low Noise
XL - Extra Low Noise

Equipment

AS - Standard equipment
DS - Desuperheater

Heating capacity 165 - 666 kW
Cooling capacity 150 - 596 kW

Safety system	To ensure high-safety-level the unit is equipped with an ATEX certified gas detector and an EC centrifugal extraction fan. The sensor, with external dedicated power supply and Modbus output signal, has an alarm threshold set at 10% of the lower flammable limit (LFL). The Propane alarm causes the immediate shutdown of the machine and the centrifugal extraction fan is switched on, which allows the ventilation of the compressor compartment and the dilution of the R290 concentration to values below the lower flammability limit.
Structure	Structure specifically designed for outdoor installation. Basement and frame in galvanised shaped sheet steel with a suitable thickness. All parts are polyester-powder painted to assure total weather resistance (RAL 7035 standard colour, others on request). LN (Low Noise) version: the panels are internally lined with sound-absorbing material. SL (Super Low Noise) version: the panels are sandwich and insulated with rock wool. XL (Extra Low Noise) version: the panels are sandwich and insulated with rock wool and silenced fans with bionic shaped blades.
Compressor with inverter	Reciprocating semi-hermetic type, fixed on anti-vibration system and complete with pressure lubrication system, oil crankcase heater, integral electronic protection, valves and flexible joints on suction and discharge. A VFD (Variable Frequency Drive) is provided in order to adapt the capacity of the reciprocating compressor to the demand. The compressor is mechanically optimized for use with Hydrocarbons.
EC Fan	Premium-Axial-Fans with an high-efficient EC (Electronically Commutated) external rotor motors, sealed in protection IP54 and thermal class THCL 155. The motor efficiency class complies with IE4.
Source heat exchanger	Finned coil made with copper pipes arranged on staggered rows, mechanically expanded inside a pack of aluminium fins offering a high exchange surface area.
User heat exchanger	Brazed plate-type heat exchanger, stainless steel AISI 316 made, complete with water differential pressure switch, air vent valve and thermally insulated with closed-cell neoprene anti-condensate material. The heat exchanger design provides high thermal exchange and high performance results, furthermore it guarantees small dimensions and easy installation and maintenance.
Electrical board	Each unit is equipped with electric panel, built, wired and fully tested at the factory. Wiring numeration and optimized layout facilitate troubleshooting. The installed components are identified by nameplates to better identify the application and the type of action. Switchboard is made according to standards IEC 204-1/EN60204-1 and it is complete with the following main components: - Main isolator switch - Door interlock safety device - Contactor and protection for compressor and fans - Cabinet minimum protection rating IP54.
Control	The microprocessor controls the unit capacity by timing the compressors and checks the operating alarms with the possibility to connect to BMS.
Refrigerant circuit	Filter drier, moisture-liquid sight glass, electronic expansion valve, high & low pressure gauge, high and low pressure transducers, high pressure switch and safety high pressure valve.

MAIN ACCESSORIES

- Anti-vibration rubber/spring mounts
- Low pressure switch
- Low pressure safety valve
- Double safety valve
- Finned pack heat exchanger Copper/Copper
- Overpressure valve / automatic by-pass
- Double water pump (stand-by) - Standard/ High pressure
- Water filter
- Double gas detector with separate electrical supply

HERA HE

Technical data

HERA HE R290		195-2-2 PV	230-2-2 PV	270-2-2 PV	300-2-2 PV	355-2-2 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	167	202	250	272	300
Total power input ⁽¹⁾	[kW]	52,5	63,8	78,9	85,6	96
COP	[-]	3,18	3,17	3,17	3,18	3,14
Heating Capacity⁽¹⁾ (XL versions)	[kW]	165	189	249	270	300
Total power input ⁽¹⁾	[kW]	52,0	63,1	78,3	84,9	95
COP	[-]	3,17	3,00	3,18	3,18	3,16
Water flow ⁽¹⁾	[m ³ /h]	28,9	35,0	43,4	47,1	52,0
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	36,8	45,0	39,5	33,6	35,0
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	27,5 / 34,7	33,3 / 42	41,2 / 52,1	44,7 / 56,5	49,4 / 62,4
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate						
SCOP (LN/SL - XL)	[W/W]	3,729 - 3,523	3,614 - 3,521	3,735 - 3,796	3,777 - 3,834	3,682 - 3,692
η _{s,h} (LN/SL - XL)	[%]	146,1 - 137,9	141,5 - 137,8	146,4 - 148,9	148,1 - 150,3	144,3 - 144,7
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate						
SCOP (LN/SL - XL)	[W/W]	3,101 - 3,134	3,118 - 3,141	3,08 - 3,118	3,088 - 3,133	3,08 - 3,078
η _{s,h} (LN/SL - XL)	[%]	121 - 122,3	121,7 - 122,6	120,2 - 121,7	120,5 - 122,3	120,2 - 120,1
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	150	176	218	237	267
Total power input ⁽²⁾	[kW]	57,9	69,8	85,9	93,4	106
EER	[-]	2,59	2,52	2,54	2,54	2,52
Cooling Capacity⁽²⁾ (XL versions)	[kW]	150	175	216	237	267
Total power input ⁽²⁾	[kW]	56,3	68,5	82,9	89,9	104
EER	[-]	2,66	2,55	2,61	2,64	2,57
Water flow ⁽²⁾	[m ³ /h]	25,8	30,4	37,5	40,8	45,9
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	31,6	36,5	32,5	29,5	29,8
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	20,6 / 31	24,3 / 36,5	30 / 45	32,6 / 49	36,7 / 55,1
Technical data						
Refrigerant / GWP	-	R290 / 3				
Charge of refrigerant	[Kg]	> 12				
Number of refrigerant circuits	N°	2				
Compressor type / quantity	-/N°	Semihhermetic reciprocating with VFD (Variable Frequency Drive) / 2				
Expansion valve type	-	Electronic				
Fans quantity / type	-	4 / Axial EC		8 / Axial EC		
Fans power input ⁽¹⁾ (total)	[kW]	1,27	1,37	2,00	2,10	2,21
Total air flow ⁽¹⁾	[m ³ /h]	45.800	47.100	84.500	85.900	87.500
Electrical data						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum absorbed power	[kW]	76,2	85,6	110	110	138
Locked rotor current - LRA	[A]	127	141	188	188	238
Maximum absorbed current (full load)	[A]	127	141	188	188	238
Solution BASE-P - with Hydronic Kit						
Pump type	-	Centrifugal				
Standard pump (1,5 bar)						
Motor efficiency	-	IE3				
Pump motor nominal power input	[kW]	2,2	3	3	3	4
Pump motor nominal absorbed current	[A]	4,7	6,4	6,4	6,4	8,7
Increased pump (3,0 bar)						
Motor efficiency	-	IE3				
Pump motor nominal power input	[kW]	4	5,5	7,5	7,5	7,5
Pump motor nominal absorbed current	[A]	8,7	10,6	13,6	13,6	13,6
Water connections						
Size (nominal external diameter)	[inch]	3" (DN 80)	3" (DN 80)	3" (DN 80)	4" (DN 100)	4" (DN 100)
Noise levels⁽³⁾						
Total sound power (LN version)	[db(A)]	86	87	91	92	93
Total sound pressure (LN version) - at 1 m distance	[db(A)]	67	68	71	72	73
Total sound pressure (LN version) - at 10 m distance	[db(A)]	54	55	59	60	61
Total sound power (SL version)	[db(A)]	85	86	90	91	92
Total sound pressure (SL version) - at 1 m distance	[db(A)]	66	67	70	71	72
Total sound pressure (SL version) - at 10 m distance	[db(A)]	53	54	58	59	60
Total sound power (XL version)	[db(A)]	83	84	88	89	90
Total sound pressure (XL version) - at 1 m distance	[db(A)]	64	65	68	69	70
Total sound pressure (XL version) - at 10 m distance	[db(A)]	51	52	56	57	58
Dimensions and weights - unit						
Length	[mm]	3.665	3.665	5.230	5.230	5.230
Width	[mm]	2.280	2.280	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	2.800	2.840	3.970	3.990	4.180
Shipment weight - BP/SL/AS/EC/II version	[Kg]	2.900	2.940	4.070	4.090	4.280
Shipment weight - BP/XL/AS/EC/II version	[Kg]	2.930	2.970	4.130	4.150	4.340

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202.

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202.

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA HE

Technical data

HERA HE R290		405-3-3 PV	450-3-3 PV	505-3-3 PV	530-3-3 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	376	407	450	500
Total power input ⁽¹⁾	[kW]	118	129	143	161
COP	[-]	3,19	3,16	3,15	3,11
Heating Capacity⁽¹⁾ (XL versions)	[kW]	374	401	444	496
Total power input ⁽¹⁾	[kW]	117	127	141	159
COP	[-]	3,20	3,16	3,15	3,12
Water flow ⁽¹⁾	[m ³ /h]	65,1	70,6	78,1	86,7
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	56,7	61,1	57,3	63,5
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	61,8 / 78,1	67,1 / 84,7	74,2 / 93,7	82,4 / 104
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate					
SCOP (LN/SL - XL)	[W/W]	3,76 - 3,818	3,763 - 3,8	3,684 - 3,71	3,665 - 3,67
η _{s,h} (LN/SL - XL)	[%]	147,4 - 149,7	147,5 - 149	144,4 - 145,4	143,6 - 143,8
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate					
SCOP (LN/SL - XL)	[W/W]	3,082 - 3,117	3,078 - 3,108	3,08 - 3,078	3,075 - 3,078
η _{s,h} (LN/SL - XL)	[%]	120,3 - 121,7	120,1 - 121,3	120,2 - 120,1	120 - 120,1
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	326	352	398	440
Total power input ⁽²⁾	[kW]	129	139	159	177
EER	[-]	2,53	2,53	2,50	2,49
Cooling Capacity⁽²⁾ (XL versions)	[kW]	325	350	396	441
Total power input ⁽²⁾	[kW]	124	135	154	172
EER	[-]	2,62	2,59	2,57	2,56
Water flow ⁽²⁾	[m ³ /h]	56,1	60,5	68,4	75,7
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	44,7	47,9	46,6	51,4
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	44,9 / 67,3	48,4 / 72,6	54,7 / 82,1	60,6 / 90,8
Technical data					
Refrigerant / GWP	-	R290 / 3			
Charge of refrigerant	[Kg]	> 12			
Number of refrigerant circuits	N°	3			
Compressor type / quantity	-/N°	Semihermetic reciprocating with VFD (Variable Frequency Drive) / 3			
Expansion valve type	-	Electronic			
Fans quantity / type	-	12 / Axial EC			
Fans power input ⁽¹⁾ (total)	[kW]	3,01	3,15	3,33	3,70
Total air flow ⁽¹⁾	[m ³ /h]	126.800	128.800	131.200	136.300
Electrical data					
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50			
Maximum absorbed power	[kW]	165	165	207	211
Locked rotor current - LRA	[A]	281	281	357	368
Maximum absorbed current (full load)	[A]	281	281	357	368
Solution BASE-P - with Hydronic Kit					
Pump type	-	Centrifugal			
Standard pump (1,5 bar)					
Motor efficiency	-	IE3			
Pump motor nominal power input	[kW]	5,5	5,5	5,5	5,5
Pump motor nominal absorbed current	[A]	10,6	10,6	10,6	10,6
Increased pump (3,0 bar)					
Motor efficiency	-	IE3			
Pump motor nominal power input	[kW]	9,2	9,2	9,2	11,0
Pump motor nominal absorbed current	[A]	17,2	17,2	17,2	21,3
Water connections					
Size (nominal external diameter)	[inch]	4" (DN 100)	4" (DN 100)	5" (DN 125)	5" (DN 125)
Noise levels⁽³⁾					
Total sound power (LN version)	[db(A)]	93	93	93	95
Total sound pressure (LN version) - at 1 m distance	[db(A)]	72	72	72	74
Total sound pressure (LN version) - at 10 m distance	[db(A)]	60	60	60	62
Total sound power (SL version)	[db(A)]	92	92	92	94
Total sound pressure (SL version) - at 1 m distance	[db(A)]	71	71	71	73
Total sound pressure (SL version) - at 10 m distance	[db(A)]	59	59	59	61
Total sound power (XL version)	[db(A)]	90	90	90	92
Total sound pressure (XL version) - at 1 m distance	[db(A)]	69	69	69	71
Total sound pressure (XL version) - at 10 m distance	[db(A)]	57	57	57	59
Dimensions and weights - unit					
Length	[mm]	7.475	7.475	7.475	7.475
Width	[mm]	2.280	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	5.960	5.960	6.250	6.290
Shipment weight - BP/SL/AS/EC/II version	[Kg]	6.060	6.060	6.350	6.390
Shipment weight - BP/XL/AS/EC/II version	[Kg]	6.150	6.150	6.440	6.480

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202:

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202:

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA HE

Technical data

HERA HE R290		600-4-4 PV	675-4-4 PV	710-4-4 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	543	600	666
Total power input ⁽¹⁾	[kW]	171	191	213
COP	[-]	3,18	3,14	3,13
Heating Capacity⁽¹⁾ (XL versions)	[kW]	540	591	656
Total power input ⁽¹⁾	[kW]	170	189	211
COP	[-]	3,18	3,13	3,11
Water flow ⁽¹⁾	[m ³ /h]	94	104	115
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	38,1	39,4	40,1
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	89,5 / 113	98,8 / 125	109 / 138
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate				
SCOP (LN/SL - XL)	[W/W]	3,81 - 3,869	3,67 - 3,687	3,663 - 3,699
$\eta_{s,h}$ (LN/SL - XL)	[%]	149,4 - 151,8	143,8 - 144,5	143,5 - 145
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate				
SCOP (LN/SL - XL)	[W/W]	3,116 - 3,158	3,079 - 3,085	3,081 - 3,095
$\eta_{s,h}$ (LN/SL - XL)	[%]	121,7 - 123,3	120,2 - 120,4	120,2 - 120,8
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	474	534	596
Total power input ⁽²⁾	[kW]	187	213	237
EER	[-]	2,53	2,51	2,51
Cooling Capacity⁽²⁾ (XL versions)	[kW]	474	530	591
Total power input ⁽²⁾	[kW]	179	206	231
EER	[-]	2,65	2,57	2,56
Water flow ⁽²⁾	[m ³ /h]	81,6	91,8	102
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	33,0	33,4	34,3
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	65,3 / 97,9	73,4 / 110	81,6 / 122
Technical data				
Refrigerant / GWP	-	R290 / 3		
Charge of refrigerant	[Kg]	> 12		
Number of refrigerant circuits	N°	4		
Compressor type / quantity	-/N°	Semihhermetic reciprocating with VFD (Variable Frequency Drive) / 4		
Expansion valve type	-	Electronic		
Fans quantity / type	-	16 / Axial EC		
Fans power input ⁽¹⁾ (total)	[kW]	4,21	4,43	5,01
Total air flow ⁽¹⁾	[m ³ /h]	171.800	174.900	182.700
Electrical data				
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50		
Maximum absorbed power	[kW]	220	276	281
Locked rotor current - LRA	[A]	375	476	490
Maximum absorbed current (full load)	[A]	375	476	490
Solution BASE-P - with Hydronic Kit				
Pump type	-	Centrifugal		
Standard pump (1,5 bar)				
Motor efficiency	-	IE3		
Pump motor nominal power input	[kW]	7,5	7,5	11
Pump motor nominal absorbed current	[A]	13,6	13,6	21,3
Increased pump (3,0 bar)				
Motor efficiency	-	IE3		
Pump motor nominal power input	[kW]	11,0	15,0	15,0
Pump motor nominal absorbed current	[A]	21,3	27,7	27,7
Water connections				
Size (nominal external diameter)	[inch]	5" (DN 125)	5" (DN 125)	6" (DN 150)
Noise levels⁽³⁾				
Total sound power (LN version)	[db(A)]	95	95	96
Total sound pressure (LN version) - at 1 m distance	[db(A)]	74	74	74
Total sound pressure (LN version) - at 10 m distance	[db(A)]	62	62	63
Total sound power (SL version)	[db(A)]	94	94	95
Total sound pressure (SL version) - at 1 m distance	[db(A)]	73	73	73
Total sound pressure (SL version) - at 10 m distance	[db(A)]	61	61	62
Total sound power (XL version)	[db(A)]	92	92	93
Total sound pressure (XL version) - at 1 m distance	[db(A)]	71	71	71
Total sound pressure (XL version) - at 10 m distance	[db(A)]	59	59	60
Dimensions and weights - unit				
Length	[mm]	9.615	9.615	9.615
Width	[mm]	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	7.880	8.250	8.340
Shipment weight - BP/SL/AS/EC/II version	[Kg]	7.980	8.350	8.440
Shipment weight - BP/XL/AS/EC/II version	[Kg]	8.100	8.470	8.560

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202.

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202.

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA HE+

R290
Refrigerant
R290 | GWP=3

Reversible
heat pump

Inverter

Axial fan

Semi-hermetic
piston compresso

Brazed plate
heat exchanger

160-2-2 PV ↔ 540-4-4 PV

SCOP

Very high efficiency Air-To-Water heat pump for low and medium temperatures applications



Solution

B - Base
P - Base with Pump

Version

LN - Low Noise
SL - Super Low Noise
XL - Extra Low Noise

Equipment

AS - Standard equipment
DS - Desuperheater

Heating capacity 159 - 538 kW
Cooling capacity 139 - 482 kW

Safety system	To ensure high-safety-level the unit is equipped with an ATEX certified gas detector and an EC centrifugal extraction fan. The sensor, with external dedicated power supply and Modbus output signal, has an alarm threshold set at 10% of the lower flammable limit (LFL). The Propane alarm causes the immediate shutdown of the machine and the centrifugal extraction fan is switched on, which allows the ventilation of the compressor compartment and the dilution of the R290 concentration to values below the lower flammability limit.
Structure	Structure specifically designed for outdoor installation. Basement and frame in galvanised shaped sheet steel with a suitable thickness. All parts are polyester-powder painted to assure total weather resistance (RAL 7035 standard colour, others on request). LN (Low Noise) version: the panels are internally lined with sound-absorbing material. SL (Super Low Noise) version: the panels are sandwich and insulated with rock wool. XL (Extra Low Noise) version: the panels are sandwich and insulated with rock wool and silenced fans with bionic shaped blades.
Compressor with inverter	Reciprocating semi-hermetic type, fixed on anti-vibration system and complete with pressure lubrication system, oil crankcase heater, integral electronic protection, valves and flexible joints on suction and discharge. A VFD (Variable Frequency Drive) is provided in order to adapt the capacity of the reciprocating compressor to the demand. The compressor is mechanically optimized for use with Hydrocarbons.
EC Fan	Premium-Axial-Fans with an high-efficient EC (Electronically Commutated) external rotor motors, sealed in protection IP54 and thermal class THCL 155. The motor efficiency class complies with IE4.
Source heat exchanger	Finned coil made with copper pipes arranged on staggered rows, mechanically expanded inside a pack of aluminium fins offering a high exchange surface area.
User heat exchanger	Brazed plate-type heat exchanger, stainless steel AISI 316 made, complete with water differential pressure switch, air vent valve and thermally insulated with closed-cell neoprene anti-condensate material. The heat exchanger design provides high thermal exchange and high performance results, furthermore it guarantees small dimensions and easy installation and maintenance.
Electrical board	Each unit is equipped with electric panel, built, wired and fully tested at the factory. Wiring numeration and optimized layout facilitate troubleshooting. The installed components are identified by nameplates to better identify the application and the type of action. Switchboard is made according to standards IEC 204-1/EN60204-1 and it is complete with the following main components: - Main isolator switch - Door interlock safety device - Contactor and protection for compressor and fans - Cabinet minimum protection rating IP54.
Control	The microprocessor controls the unit capacity by timing the compressors and checks the operating alarms with the possibility to connect to BMS.
Refrigerant circuit	Filter drier, moisture-liquid sight glass, electronic expansion valve, high & low pressure gauge, high and low pressure transducers, high pressure switch and safety high pressure valve.

MAIN ACCESSORIES

- Anti-vibration rubber/spring mounts
- Low pressure switch
- Low pressure safety valve
- Double safety valve
- Finned pack heat exchanger Copper/Copper
- Overpressure valve / automatic by-pass
- Double water pump (stand-by) - Standard/ High pressure
- Water filter
- Double gas detector with separate electrical supply

HERA HE+

Technical data

HERA HE+ R290		160-2-2 PV	180-2-2 PV	210-2-2 PV	235-2-2 PV	270-2-2 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	159	178	210	234	269
Total power input ⁽¹⁾	[kW]	52,8	63,6	69,5	75,4	87,7
COP	[-]	3,01	2,80	3,02	3,10	3,07
Heating Capacity⁽¹⁾ (XL versions)	[kW]	159	177	211	231	267
Total power input ⁽¹⁾	[kW]	52,6	63,1	69,1	74,7	87,1
COP	[-]	3,02	2,81	3,05	3,09	3,07
Water flow ⁽¹⁾	[m ³ /h]	27,6	30,9	36,3	40,5	46,6
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	45,8	55,0	59,7	27,8	34,5
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	26,2 / 33,1	29,4 / 37,1	34,5 / 43,6	38,5 / 48,6	44,3 / 55,9
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate						
SCOP (LN/SL - XL)	[W/W]	4,033 - 4,087	3,821 - 3,73	3,876 - 3,964	4,024 - 4,122	3,964 - 4,05
η _{s,h} (LN/SL - XL)	[%]	158,3 - 160,5	149,9 - 146,2	152 - 155,6	158 - 161,9	155,6 - 159
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate						
SCOP (LN/SL - XL)	[W/W]	3,391 - 3,433	3,355 - 3,387	3,317 - 3,374	3,355 - 3,412	3,314 - 3,364
η _{s,h} (LN/SL - XL)	[%]	132,6 - 134,3	131,2 - 132,5	129,7 - 132	131,2 - 133,5	129,6 - 131,6
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	140	162	186	208	238
Total power input ⁽²⁾	[kW]	56,6	67,4	77,8	87,2	101
EER	[-]	2,47	2,40	2,39	2,39	2,36
Cooling Capacity⁽²⁾ (XL versions)	[kW]	139	161	185	207	241
Total power input ⁽²⁾	[kW]	55,2	65,9	74,4	83,9	98,5
EER	[-]	2,52	2,44	2,49	2,47	2,45
Water flow ⁽²⁾	[m ³ /h]	24,1	27,8	32,0	35,8	40,9
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	38,5	48,7	50,6	24,0	29,5
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	19,3 / 28,9	22,2 / 33,4	25,6 / 38,4	28,6 / 43	32,7 / 49,1
Technical data						
Refrigerant / GWP	-	R290 / 3				
Charge of refrigerant	[Kg]	> 12				
Number of refrigerant circuits	N°	2				
Compressor type / quantity	-/N°	Semihhermetic reciprocating with VFD (Variable Frequency Drive) / 2				
Expansion valve type	-	Electronic				
Fans quantity / type	-	4 / Axial EC		8 / Axial EC		
Fans power input ⁽¹⁾ (total)	[kW]	1,28	1,35	2,11	2,12	2,28
Total air flow ⁽¹⁾	[m ³ /h]	46.800	47.700	87.000	87.300	89.700
Electrical data						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum absorbed power	[kW]	68,4	82,4	96,8	109	127
Locked rotor current - LRA	[A]	122	143	167	186	231
Maximum absorbed current (full load)	[A]	122	143	167	186	231
Solution BASE-P - with Hydronic Kit						
Pump type	-	Centrifugal				
Standard pump (1,5 bar)						
Motor efficiency	-	IE3				
Pump motor nominal power input	[kW]	2,2	2,2	3,0	3,0	3,0
Pump motor nominal absorbed current	[A]	4,7	4,7	6,4	6,4	6,4
Increased pump (3,0 bar)						
Motor efficiency	-	IE3				
Pump motor nominal power input	[kW]	4,0	4,0	7,5	7,5	7,5
Pump motor nominal absorbed current	[A]	8,7	8,7	13,6	13,6	13,6
Water connections						
Size (nominal external diameter)	[inch]	3" (DN 80)	3" (DN 80)	3" (DN 80)	3" (DN 80)	4" (DN 100)
Noise levels⁽³⁾						
Total sound power (LN version)	[db(A)]	86	87	91	92	93
Total sound pressure (LN version) - at 1 m distance	[db(A)]	67	68	71	72	73
Total sound pressure (LN version) - at 10 m distance	[db(A)]	54	55	59	60	61
Total sound power (SL version)	[db(A)]	85	86	90	91	92
Total sound pressure (SL version) - at 1 m distance	[db(A)]	66	67	70	71	72
Total sound pressure (SL version) - at 10 m distance	[db(A)]	53	54	58	59	60
Total sound power (XL version)	[db(A)]	83	84	88	89	90
Total sound pressure (XL version) - at 1 m distance	[db(A)]	64	65	68	69	70
Total sound pressure (XL version) - at 10 m distance	[db(A)]	51	52	56	57	58
Dimensions and weights - unit						
Length	[mm]	3.665	3.665	5.230	5.230	5.230
Width	[mm]	2.280	2.280	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	2.800	2.840	3.970	3.990	4.180
Shipment weight - BP/SL/AS/EC/II version	[Kg]	2.900	2.940	4.070	4.090	4.280
Shipment weight - BP/XL/AS/EC/II version	[Kg]	2.930	2.970	4.130	4.150	4.340

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202.

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202.

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA HE+

Technical data

HERA HE+ R290		315-3-3 PV	350-3-3 PV	405-3-3 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	316	351	403
Total power input ⁽¹⁾	[kW]	104	113	132
COP	[-]	3,04	3,11	3,05
Heating Capacity⁽¹⁾ (XL versions)	[kW]	316	348	400
Total power input ⁽¹⁾	[kW]	103	112	131
COP	[-]	3,07	3,11	3,05
Water flow ⁽¹⁾	[m ³ /h]	54,8	60,8	69,9
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	59,0	55,0	63,0
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	52,1 / 65,8	57,8 / 73	66,4 / 83,9
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate				
SCOP (LN/SL - XL)	[W/W]	4,000 - 4,076	4,018 - 4,107	3,951 - 4,007
$\eta_{s,h}$ (LN/SL - XL)	[%]	157 - 160	157,7 - 161,3	155 - 157,3
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate				
SCOP (LN/SL - XL)	[W/W]	3,328 - 3,388	3,341 - 3,399	3,301 - 3,343
$\eta_{s,h}$ (LN/SL - XL)	[%]	130,1 - 132,5	130,6 - 133	129,1 - 130,7
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	281	318	366
Total power input ⁽²⁾	[kW]	116	132	153
EER	[-]	2,42	2,41	2,39
Cooling Capacity⁽²⁾ (XL versions)	[kW]	279	317	366
Total power input ⁽²⁾	[kW]	111	127	148
EER	[-]	2,51	2,50	2,47
Water flow ⁽²⁾	[m ³ /h]	48,3	54,8	62,9
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	48,1	45,9	52,5
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	38,6 / 58	43,8 / 65,8	50,3 / 75,5
Technical data				
Refrigerant / GWP	-	R290 / 3		
Charge of refrigerant	[Kg]	> 12		
Number of refrigerant circuits	N°	3		
Compressor type / quantity	-/N°	Semihermetic reciprocating with VFD (Variable Frequency Drive) / 3		
Expansion valve type	-	Electronic		
Fans quantity / type	-	12 / Axial EC		
Fans power input ⁽¹⁾ (total)	[kW]	3,03	3,16	3,41
Total air flow ⁽¹⁾	[m ³ /h]	128.700	130.800	134.400
Electrical data				
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50		
Maximum absorbed power	[kW]	145	163	190
Locked rotor current - LRA	[A]	251	279	346
Maximum absorbed current (full load)	[A]	251	279	346
Solution BASE-P - with Hydronic Kit				
Pump type	-	Centrifugal		
Standard pump (1,5 bar)				
Motor efficiency	-	IE3		
Pump motor nominal power input	[kW]	4,0	5,5	5,5
Pump motor nominal absorbed current	[A]	8,7	10,6	10,6
Increased pump (3,0 bar)				
Motor efficiency	-	IE3		
Pump motor nominal power input	[kW]	7,5	9,2	9,2
Pump motor nominal absorbed current	[A]	13,6	17,2	17,2
Water connections				
Size (nominal external diameter)	[inch]	4" (DN 100)	4" (DN 100)	4" (DN 100)
Noise levels⁽³⁾				
Total sound power (LN version)	[db(A)]	93	93	93
Total sound pressure (LN version) - at 1 m distance	[db(A)]	72	72	72
Total sound pressure (LN version) - at 10 m distance	[db(A)]	60	60	60
Total sound power (SL version)	[db(A)]	92	92	92
Total sound pressure (SL version) - at 1 m distance	[db(A)]	71	71	71
Total sound pressure (SL version) - at 10 m distance	[db(A)]	59	59	59
Total sound power (XL version)	[db(A)]	90	90	90
Total sound pressure (XL version) - at 1 m distance	[db(A)]	69	69	69
Total sound pressure (XL version) - at 10 m distance	[db(A)]	57	57	57
Dimensions and weights - unit				
Length	[mm]	7.475	7.475	7.475
Width	[mm]	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	5.960	5.960	6.250
Shipment weight - BP/SL/AS/EC/II version	[Kg]	6.060	6.060	6.350
Shipment weight - BP/XL/AS/EC/II version	[Kg]	6.150	6.150	6.440

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202.

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202.

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA HE+

Technical data

HERA HE+ R290		470-4-4 PV	540-4-4 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	467	538
Total power input ⁽¹⁾	[kW]	151	175
COP	[-]	3,09	3,07
Heating Capacity⁽¹⁾ (XL versions)	[kW]	462	535
Total power input ⁽¹⁾	[kW]	149	173
COP	[-]	3,10	3,09
Water flow ⁽¹⁾	[m ³ /h]	81,0	93,3
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	32,2	36,6
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	77 / 97,2	88,6 / 112
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate			
SCOP (LN/SL - XL)	[W/W]	4,083 - 4,175	4,035 - 4,089
$\eta_{s,h}$ (LN/SL - XL)	[%]	160,3 - 164	158,4 - 160,5
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate			
SCOP (LN/SL - XL)	[W/W]	3,386 - 3,44	3,355 - 3,39
$\eta_{s,h}$ (LN/SL - XL)	[%]	132,5 - 134,6	131,2 - 132,6
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	416	482
Total power input ⁽²⁾	[kW]	174	202
EER	[-]	2,39	2,39
Cooling Capacity⁽²⁾ (XL versions)	[kW]	414	477
Total power input ⁽²⁾	[kW]	168	196
EER	[-]	2,46	2,43
Water flow ⁽²⁾	[m ³ /h]	71,6	82,9
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	27,6	29,8
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	57,3 / 85,9	66,3 / 99,5
Technical data			
Refrigerant / GWP	-	R290 / 3	
Charge of refrigerant	[Kg]	> 12	
Number of refrigerant circuits	N°	4	
Compressor type / quantity	-/N°	Semihermetic reciprocating with VFD (Variable Frequency Drive) / 4	
Expansion valve type	-	Electronic	
Fans quantity / type	-	16 / Axial EC	
Fans power input ⁽¹⁾ (total)	[kW]	4,24	4,56
Total air flow ⁽¹⁾	[m ³ /h]	174.700	179.300
Electrical data			
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50	
Maximum absorbed power	[kW]	218	254
Locked rotor current - LRA	[A]	372	462
Maximum absorbed current (full load)	[A]	372	462
Solution BASE-P - with Hydronic Kit			
Pump type	-	Centrifugal	
Standard pump (1,5 bar)			
Motor efficiency	-	IE3	
Pump motor nominal power input	[kW]	5,5	7,5
Pump motor nominal absorbed current	[A]	10,6	13,6
Increased pump (3,0 bar)			
Motor efficiency	-	IE3	
Pump motor nominal power input	[kW]	9,2	11,0
Pump motor nominal absorbed current	[A]	17,2	21,3
Water connections			
Size (nominal external diameter)	[inch]	5" (DN 125)	5" (DN 125)
Noise levels⁽³⁾			
Total sound power (LN version)	[db(A)]	95	95
Total sound pressure (LN version) - at 1 m distance	[db(A)]	74	74
Total sound pressure (LN version) - at 10 m distance	[db(A)]	62	62
Total sound power (SL version)	[db(A)]	94	94
Total sound pressure (SL version) - at 1 m distance	[db(A)]	73	73
Total sound pressure (SL version) - at 10 m distance	[db(A)]	61	61
Total sound power (XL version)	[db(A)]	92	92
Total sound pressure (XL version) - at 1 m distance	[db(A)]	71	71
Total sound pressure (XL version) - at 10 m distance	[db(A)]	59	59
Dimensions and weights - unit			
Length	[mm]	9.615	9.615
Width	[mm]	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550
Height (XL)	[mm]	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	7.880	8.250
Shipment weight - BP/SL/AS/EC/II version	[Kg]	7.980	8.350
Shipment weight - BP/XL/AS/EC/II version	[Kg]	8.100	8.470

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202.

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202.

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA HT

R290
Refrigerant
R290 | GWP=3

Reversible
heat pump

Inverter

Axial fan

Semi-hermetic
piston compresso

Brazed plate
heat exchanger

170-2-2 PV ↔ 680-4-4 PV

SCOP

High efficiency Air-To-Water heat pump for low, medium and high temperatures applications



Solution

B - Base
P - Base with Pump

Version

LN - Low Noise
SL - Super Low Noise
XL - Extra Low Noise

Equipment

AS - Standard equipment
DS - Desuperheater

Heating capacity 182 - 714 kW
Cooling capacity 164 - 653 kW

Safety system	To ensure high-safety-level the unit is equipped with an ATEX certified gas detector and an EC centrifugal extraction fan. The sensor, with external dedicated power supply and Modbus output signal, has an alarm threshold set at 10% of the lower flammable limit (LFL). The Propane alarm causes the immediate shutdown of the machine and the centrifugal extraction fan is switched on, which allows the ventilation of the compressor compartment and the dilution of the R290 concentration to values below the lower flammability limit.
Structure	Structure specifically designed for outdoor installation. Basement and frame in galvanised shaped sheet steel with a suitable thickness. All parts are polyester-powder painted to assure total weather resistance (RAL 7035 standard colour, others on request). LN (Low Noise) version: the panels are internally lined with sound-absorbing material. SL (Super Low Noise) version: the panels are sandwich and insulated with rock wool. XL (Extra Low Noise) version: the panels are sandwich and insulated with rock wool and silenced fans with bionic shaped blades.
Compressor with inverter	Reciprocating semi-hermetic type, fixed on anti-vibration system and complete with pressure lubrication system, oil crankcase heater, integral electronic protection, valves and flexible joints on suction and discharge. A VFD (Variable Frequency Drive) is provided in order to adapt the capacity of the reciprocating compressor to the demand. The compressor is mechanically optimized for use with Hydrocarbons.
EC Fan	Premium-Axial-Fans with an high-efficient EC (Electronically Commutated) external rotor motors, sealed in protection IP54 and thermal class THCL 155. The motor efficiency class complies with IE4.
Source heat exchanger	Finned coil made with copper pipes arranged on staggered rows, mechanically expanded inside a pack of aluminium fins offering a high exchange surface area.
User heat exchanger	Brazed plate-type heat exchanger, stainless steel AISI 316 made, complete with water differential pressure switch, air vent valve and thermally insulated with closed-cell neoprene anti-condensate material. The heat exchanger design provides high thermal exchange and high performance results, furthermore it guarantees small dimensions and easy installation and maintenance.
Electrical board	Each unit is equipped with electric panel, built, wired and fully tested at the factory. Wiring numeration and optimized layout facilitate troubleshooting. The installed components are identified by nameplates to better identify the application and the type of action. Switchboard is made according to standards IEC 204-1/EN60204-1 and it is complete with the following main components: - Main isolator switch - Door interlock safety device - Contactor and protection for compressor and fans - Cabinet minimum protection rating IP54.
Control	The microprocessor controls the unit capacity by timing the compressors and checks the operating alarms with the possibility to connect to BMS.
Refrigerant circuit	Filter drier, moisture-liquid sight glass, electronic expansion valve, high & low pressure gauge, high and low pressure transducers, high pressure switch and safety high pressure valve.

MAIN ACCESSORIES

- Anti-vibration rubber/spring mounts
- Low pressure switch
- Low pressure safety valve
- Double safety valve
- Finned pack heat exchanger Copper/Copper
- Overpressure valve / automatic by-pass
- Double water pump (stand-by) - Standard/ High pressure
- Water filter
- Double gas detector with separate electrical supply

HERA HT

Technical data

HERA HT R290		170-2-2 PV	205-2-2 PV	245-2-2 PV	280-2-2 PV	310-2-2 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	182	200	252	295	324
Total power input ⁽¹⁾	[kW]	61,0	71,7	83,0	96,3	107
COP	[-]	2,98	2,79	3,04	3,06	3,03
Heating Capacity⁽¹⁾ (XL versions)	[kW]	183	201	253	297	326
Total power input ⁽¹⁾	[kW]	61,0	71,8	83,1	96,4	107
COP	[-]	3,00	2,80	3,04	3,08	3,05
Water flow ⁽¹⁾	[m ³ /h]	31,5	34,7	43,8	51,2	56,2
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	45,3	46,6	42,9	41,3	42,4
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	29,9/37,8	33,0/41,6	41,6/52,6	48,6/61,4	53,4/67,4
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate						
SCOP (LN/SL - XL)	[W/W]	3,555 - 3,570	3,561 - 3,577	3,901 - 3,926	3,969 - 3,998	3,968 - 3,991
$\eta_{s,h}$ (LN/SL - XL)	[%]	139,2 - 139,8	139,4 - 140,1	153,0 - 154,0	155,8 - 156,9	155,7 - 156,7
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate						
SCOP (LN/SL - XL)	[W/W]	3,285 - 3,300	2,969 - 2,988	3,291 - 3,310	3,350 - 3,366	3,329 - 3,343
$\eta_{s,h}$ (LN/SL - XL)	[%]	128,4 - 129,0	115,7 - 116,5	128,6 - 129,4	131,0 - 131,6	130,2 - 130,7
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	164	189	229	270	295
Total power input ⁽²⁾	[kW]	71,3	84,0	96,7	112,0	125
EER	[-]	2,30	2,25	2,37	2,41	2,36
Cooling Capacity⁽²⁾ (XL versions)	[kW]	164	189	230	270	296
Total power input ⁽²⁾	[kW]	70,8	83,3	95,9	111	124
EER	[-]	2,32	2,27	2,40	2,43	2,39
Water flow ⁽²⁾	[m ³ /h]	28,2	32,5	39,4	46,3	50,7
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	39,2	43,8	37,8	39,0	38,0
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	22,6/33,8	26,0/39,0	31,5/47,3	37,0/55,6	40,6/60,8
Technical data						
Refrigerant / GWP	-	R290 / 3				
Charge of refrigerant	[Kg]	> 12				
Number of refrigerant circuits	N°	2				
Compressor type / quantity	-/N°	Semihhermetic reciprocating with VFD (Variable Frequency Drive) / 2				
Expansion valve type	-	Electronic				
Fans quantity / type	-	4 / Axial EC		8 / Axial EC		
Fans power input ⁽¹⁾ (total)	[kW]	1,13	1,26	1,78	1,98	2,10
Total air flow ⁽¹⁾	[m ³ /h]	42.080	43.690	77.510	80.350	82.050
Electrical data						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum absorbed power	[kW]	93,0	112	132	153	170
Locked rotor current - LRA	[A]	148	179	209	243	271
Maximum absorbed current (full load)	[A]	148	179	209	243	271
Solution BASE-P - with Hydronic Kit						
Pump type	-	Centrifugal				
Standard pump (1,5 bar)						
Motor efficiency	-	IE3				
Pump motor nominal power input	[kW]	2,2	3	3	3	4
Pump motor nominal absorbed current	[A]	4,7	6,4	6,4	6,4	8,7
Increased pump (3,0 bar)						
Motor efficiency	-	IE3				
Pump motor nominal power input	[kW]	4	5,5	7,5	7,5	7,5
Pump motor nominal absorbed current	[A]	8,7	10,6	13,6	13,6	13,6
Water connections						
Size (nominal external diameter)	[inch]	3" (DN 80)	3" (DN 80)	3" (DN 80)	4" (DN 100)	4" (DN 100)
Noise levels⁽³⁾						
Total sound power (LN version)	[db(A)]	86	87	91	92	93
Total sound pressure (LN version) - at 1 m distance	[db(A)]	67	68	71	72	73
Total sound pressure (LN version) - at 10 m distance	[db(A)]	54	55	59	60	61
Total sound power (SL version)	[db(A)]	85	86	90	91	92
Total sound pressure (SL version) - at 1 m distance	[db(A)]	66	67	70	71	72
Total sound pressure (SL version) - at 10 m distance	[db(A)]	53	54	58	59	60
Total sound power (XL version)	[db(A)]	83	84	88	89	90
Total sound pressure (XL version) - at 1 m distance	[db(A)]	64	65	68	69	70
Total sound pressure (XL version) - at 10 m distance	[db(A)]	51	52	56	57	58
Dimensions and weights - unit						
Length	[mm]	3.665	3.665	5.230	5.230	5.230
Width	[mm]	2.280	2.280	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	2.800	2.840	3.970	3.990	4.180
Shipment weight - BP/SL/AS/EC/II version	[Kg]	2.900	2.940	4.070	4.090	4.280
Shipment weight - BP/XL/AS/EC/II version	[Kg]	2.930	2.970	4.130	4.150	4.340

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202:

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202:

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA HT

Technical data

HERA HT R290		365-3-3 PV	425-3-3 PV	465-3-3 PV	510-3-3 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	379	443	486	532
Total power input ⁽¹⁾	[kW]	125	145	161	175
COP	[-]	3,03	3,06	3,02	3,04
Heating Capacity⁽¹⁾ (XL versions)	[kW]	381	444	489	535
Total power input ⁽¹⁾	[kW]	125	145	161	176
COP	[-]	3,05	3,06	3,04	3,04
Water flow ⁽¹⁾	[m ³ /h]	65,8	76,8	84,3	92,3
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	57,3	66,2	62,0	67,6
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	62,5/79,0	73,0/92,2	80,1/101	87,7/111
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate					
SCOP (LN/SL - XL)	[W/W]	3,838 - 3,860	3,844 - 3,866	3,885 - 3,908	3,581 - 3,597
η _{s,h} (LN/SL - XL)	[%]	150,5 - 151,4	150,8 - 151,6	152,4 - 153,3	140,3 - 140,9
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate					
SCOP (LN/SL - XL)	[W/W]	3,284 - 3,303	3,318 - 3,334	3,312 - 3,328	3,344 - 3,360
η _{s,h} (LN/SL - XL)	[%]	128,4 - 129,1	129,7 - 130,3	129,5 - 130,1	130,8 - 131,4
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	344	400	440	482
Total power input ⁽²⁾	[kW]	145	168	187	204
EER	[-]	2,37	2,38	2,35	2,36
Cooling Capacity⁽²⁾ (XL versions)	[kW]	345	402	442	484
Total power input ⁽²⁾	[kW]	144	167	186	203
EER	[-]	2,40	2,41	2,38	2,38
Water flow ⁽²⁾	[m ³ /h]	59,2	68,8	75,7	82,8
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	50,6	57,6	54,7	59,4
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	47,4/71,0	55,0/82,6	60,6/90,8	66,2/99,4
Technical data					
Refrigerant / GWP	-	R290 / 3			
Charge of refrigerant	[Kg]	> 12			
Number of refrigerant circuits	N°	3			
Compressor type / quantity	-/N°	Semihermetic reciprocating with VFD (Variable Frequency Drive) / 3			
Expansion valve type	-	Electronic			
Fans quantity / type	-	12 / Axial EC			
Fans power input ⁽¹⁾ (total)	[kW]	2,69	2,94	3,15	3,36
Total air flow ⁽¹⁾	[m ³ /h]	116.500	120.300	123.100	125.900
Electrical data					
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50			
Maximum absorbed power	[kW]	197	229	255	276
Locked rotor current - LRA	[A]	314	365	407	440
Maximum absorbed current (full load)	[A]	314	365	407	440
Solution BASE-P - with Hydronic Kit					
Pump type	-	Centrifugal			
Standard pump (1,5 bar)					
Motor efficiency	-	IE3			
Pump motor nominal power input	[kW]	5,5	5,5	5,5	5,5
Pump motor nominal absorbed current	[A]	10,6	10,6	10,6	10,6
Increased pump (3,0 bar)					
Motor efficiency	-	IE3			
Pump motor nominal power input	[kW]	9,2	9,2	9,2	11,0
Pump motor nominal absorbed current	[A]	17,2	17,2	17,2	21,3
Water connections					
Size (nominal external diameter)	[inch]	4" (DN 100)	4" (DN 100)	5" (DN 125)	5" (DN 125)
Noise levels⁽³⁾					
Total sound power (LN version)	[db(A)]	93	93	93	95
Total sound pressure (LN version) - at 1 m distance	[db(A)]	72	72	72	74
Total sound pressure (LN version) - at 10 m distance	[db(A)]	60	60	60	62
Total sound power (SL version)	[db(A)]	92	92	92	94
Total sound pressure (SL version) - at 1 m distance	[db(A)]	71	71	71	73
Total sound pressure (SL version) - at 10 m distance	[db(A)]	59	59	59	61
Total sound power (XL version)	[db(A)]	90	90	90	92
Total sound pressure (XL version) - at 1 m distance	[db(A)]	69	69	69	71
Total sound pressure (XL version) - at 10 m distance	[db(A)]	57	57	57	59
Dimensions and weights - unit					
Length	[mm]	7.475	7.475	7.475	7.475
Width	[mm]	2.280	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	5.960	5.960	6.250	6.290
Shipment weight - BP/SL/AS/EC/II version	[Kg]	6.060	6.060	6.350	6.390
Shipment weight - BP/XL/AS/EC/II version	[Kg]	6.150	6.150	6.440	6.480

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202:

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202:

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website

HERA HT

Technical data

HERA HT R290		560-4-4 PV	620-4-4 PV	680-4-4 PV
Heating Capacity⁽¹⁾ (LN/SL versions)	[kW]	591	648	710
Total power input ⁽¹⁾	[kW]	192	214	232
COP	[-]	3,08	3,03	3,06
Heating Capacity⁽¹⁾ (XL versions)	[kW]	593	651	714
Total power input ⁽¹⁾	[kW]	193	214	233
COP	[-]	3,07	3,04	3,06
Water flow ⁽¹⁾	[m ³ /h]	102	112	123
User circuit pressure drop ⁽¹⁾ - Base version	[kPa]	45,2	46,3	46,3
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	96,9/122	106/134	117/148
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate				
SCOP (LN/SL - XL)	[W/W]	3,975 - 3,999	3,988 - 3,998	3,676 - 3,692
$\eta_{s,h}$ (LN/SL - XL)	[%]	156,0 - 157,0	156,5 - 156,9	144,0 - 144,7
Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate				
SCOP (LN/SL - XL)	[W/W]	3,373 - 3,389	3,355 - 3,369	3,400 - 3,417
$\eta_{s,h}$ (LN/SL - XL)	[%]	131,9 - 132,6	131,2 - 131,8	133,0 - 133,7
Cooling Capacity⁽²⁾ (LN/SL versions)	[kW]	539	590	650
Total power input ⁽²⁾	[kW]	225	250	273
EER	[-]	2,40	2,36	2,38
Cooling Capacity⁽²⁾ (XL versions)	[kW]	541	592	653
Total power input ⁽²⁾	[kW]	223	248	271
EER	[-]	2,43	2,39	2,41
Water flow ⁽²⁾	[m ³ /h]	92,7	101,0	112
User circuit pressure drop ⁽²⁾ - Base version	[kPa]	42,8	41,7	42,3
Min / Max water flow (heat exchanger, user side)	[m ³ /h]	74,2/111	80,8/121	89,6/134
Technical data				
Refrigerant / GWP	-	R290 / 3		
Charge of refrigerant	[Kg]	> 12		
Number of refrigerant circuits	N°	4		
Compressor type / quantity	-/N°	Semihhermetic reciprocating with VFD (Variable Frequency Drive) / 4		
Expansion valve type	-	Electronic		
Fans quantity / type	-	16 / Axial EC		
Fans power input ⁽¹⁾ (total)	[kW]	3,95	4,20	4,49
Total air flow ⁽¹⁾	[m ³ /h]	160.700	164.100	168.000
Electrical data				
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50		
Maximum absorbed power	[kW]	306	340	368
Locked rotor current - LRA	[A]	486	542	586
Maximum absorbed current (full load)	[A]	486	542	586
Solution BASE-P - with Hydronic Kit				
Pump type	-	Centrifugal		
Standard pump (1,5 bar)				
Motor efficiency	-	IE3		
Pump motor nominal power input	[kW]	7,5	7,5	11
Pump motor nominal absorbed current	[A]	13,6	13,6	21,3
Increased pump (3,0 bar)				
Motor efficiency	-	IE3		
Pump motor nominal power input	[kW]	11,0	15,0	15,0
Pump motor nominal absorbed current	[A]	21,3	27,7	27,7
Water connections				
Size (nominal external diameter)	[inch]	5" (DN 125)	5" (DN 125)	6" (DN 150)
Noise levels⁽³⁾				
Total sound power (LN version)	[db(A)]	95	95	96
Total sound pressure (LN version) - at 1 m distance	[db(A)]	74	74	74
Total sound pressure (LN version) - at 10 m distance	[db(A)]	62	62	63
Total sound power (SL version)	[db(A)]	94	94	95
Total sound pressure (SL version) - at 1 m distance	[db(A)]	73	73	73
Total sound pressure (SL version) - at 10 m distance	[db(A)]	61	61	62
Total sound power (XL version)	[db(A)]	92	92	93
Total sound pressure (XL version) - at 1 m distance	[db(A)]	71	71	71
Total sound pressure (XL version) - at 10 m distance	[db(A)]	59	59	60
Dimensions and weights - unit				
Length	[mm]	9.615	9.615	9.615
Width	[mm]	2.280	2.280	2.280
Height (LN, SL)	[mm]	2.550	2.550	2.550
Height (XL)	[mm]	2.610	2.610	2.610
Shipment weight - BP/LN/AS/EC/II version	[Kg]	7.880	8.250	8.340
Shipment weight - BP/SL/AS/EC/II version	[Kg]	7.980	8.350	8.440
Shipment weight - BP/XL/AS/EC/II version	[Kg]	8.100	8.470	8.560

Reference conditions:

(1) Outdoor ambient air = +7 °C / 87% r.h. - Condenser fluid temperature IN/OUT = 40/45 °C - Fluid: water - Results according to UNI EN 14511-202.

(2) Condenser air intake temperature = 35 °C - Evaporator fluid temperature IN/OUT = 12/7 °C - Fluid: water - Results according to UNI EN 14511-202.

(3) Sound power level in compliance with ISO 3744 - Sound pressure level (average) at 10 meter distance, unit in a free field on a reflective surface; non-binding value obtained from the sound power level

Compliance with "Eco-Design"

The units comply with the European Directive 2009/125/EU, the Commission Regulation (EU) No 811/2013, No 813/2013 and with the Harmonized Standards

The relevant information related to each model (eg.: SCOP, Seasonal Space Heating Energy Efficiency, Annual electricity consumption, ...) are published on our website