

# Datasheet HYDRA

R290



Water-To-Water Heat Pump reversible on the water side  
for comfort applications

Nominal heating capacity: 18-270 kW

Nominal cooling capacity: 16-215 kW



**EUROKLIMAT**  
Let's go Natural

# HYDRA



Refrigerant  
R290 | GWP=3



Brazed plate  
heat exchanger



Semi-hermetic  
piston compressor



Reversible  
heat pump



SCOP

15-1-1 ↔ 220-2-2

Water to water heat pumps with reciprocating compressors for comfort applications up to 60 °C



## Solution

B - Base

## Sound version

ST - Standard

LN - Low Noise

SL - Super Low Noise

## Equipment

AS - Standard equipment

DS - Desuperheater

Heating capacity 18 - 253 kW

Cooling capacity 16 - 208 kW

### Safety system

To ensure a high level of safety throughout the useful life of the selected propane unit, special measures have been introduced that make this product unique. In fact, the refrigeration circuit is watertight and sufficiently robust, the pipes have been designed to have few joints and welds and all the materials used are compatible with the R290 refrigerant (propane). The electrical panel is installed in a separate compartment and some of the most important components are ATEX certified. In addition, the unit is equipped with a refrigerant gas leak detector and with a centrifugal suction expulsion fan, both ATEX certified.

### Refrigerant charge

Maximum allowable charge of Refrigerating systems and heat pumps should be evaluated according to EN378:2016 that is a safety and environmental standard published by CEN that provides guidance for Design, Construction, Installation, Operation and Maintenance of Refrigerating systems and heat pumps.

### Structure

Structure specifically designed and built to guarantee total resistance to atmospheric agents and corrosion. Basement and panels made of galvanized steel sheet, oven-painted with polyurethane powders. Frame made of anodized aluminium profiles, with aluminium alloy corner joints that guarantee excellent mechanical resistance and low weight. LN (Low Noise) version: the panels are internally lined with sound-absorbing material. SL (Super Low Noise) version: the panels are sandwich and insulated with rock wool.

### Compressor

Reciprocating semi-hermetic type compressor equipped with: electronic control module and protection of the electric motor (installed inside the electrical panel); oil charge; oil level sight glass and oil crankcase heater; anti-vibration rubber supports; anti-vibration pipes (suction and discharge); suction and discharge valves. The compressor can be supplied with one or more RSH capacity control heads to guarantee an adaptation of the cooling capacity in case of thermal load's reduction: please see the list of accessories for further information.

### Water heat exchangers

Brazed plate-type heat exchangers, stainless steel AISI 316 made, complete with water differential pressure switch, air vent valve and thermally insulated with closed-cell neoprene anti-condensate material. The heat exchangers design provides high thermal exchange and high performance results, furthermore it guarantees small dimensions and easy installation and maintenance.

### Electrical board

Each unit is equipped with electric panel, built, wired and fully tested at the factory. Wiring numeration and optimized layout facilitate troubleshooting. The installed components are identified by nameplates to better identify the application and the type of action. Switchboard is made according to standards IEC 204-1/EN60204-1 and it is complete with the following main components: - Main isolator switch - Door interlock safety device - Contactor and protection for compressor and fans - Cabinet minimum protection rating IP54.

To ensure higher level of security, the cabinet is outside the machine and positioned on one side of the unit. The propane sensor is equipped with separate power supply: this power supply must always be guaranteed in order to ensure the monitoring of any leakage.

### Control

The programmable electronic microprocessor control system allows you to automatically adjust the thermal or cooling power supplied by the unit and to manage malfunction alarms. Thanks to a multitasking operating system and the adoption of standard, local and remote connectivity protocols, the selected controller is a powerful control system that can be easily interfaced with the most common Building Management Systems (BMS) on the market.

### Refrigerant circuit

Filter drier, moisture-liquid sight glass, electronic expansion valve, high & low pressure gauge, high and low pressure transducers, high pressure switch, safety high pressure valve (when required by EN 378-2016 standard).

### Water circuit

Base version: as interface to the plant, includes the water fittings of the evaporator only.

## MAIN ACCESSORIES

- Anti-vibration rubber/bell mounts
- Stainless steel panels (AISI 304)
- Double safety valve with changeover valve
- Electronic flow switch hydraulic circuit - Evaporator
- Flanges and counter-flanges for water fittings
- Hydraulic circuit pipes in stainless steel
- Water filter
- RSH Capacity Control head / Inverter driven compressor
- Double gas detector with separate electrical supply
- Energy meter for measuring the electric energy consumed
- Cloud GATE" device for monitoring and remote management
- UNIT COLLECT - Cascade unit management system

# HYDRA

## Technical data

HYDRA R290 range		15-1-1	25-1-1	35-1-1	45-1-1	55-1-1
<b>P BP/**/AS/BP/*S version</b>						
Heating capacity <sup>(1)</sup>	[kW]	18,3	29,6	36,6	53,5	63,6
Total power input <sup>(1)</sup>	[kW]	4,53	7,50	9,49	13,4	15,7
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	4,04	3,95	3,86	3,99	4,05
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	3,17	5,13	6,32	9,26	11,00
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	40,4	47,8	49,6	30,0	40,3
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	4,00	6,42	7,83	11,60	13,80
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	47,5	55,3	47,6	57,7	46,9
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	5,794	5,938	5,651	5,706	5,759
η <sub>s,h</sub>	[%]	223,8	229,5	218,0	220,2	222,4
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,546	4,537	4,393	4,468	4,543
η <sub>s,h</sub>	[%]	173,9	173,5	167,7	170,7	173,7
Cooling capacity <sup>(2)</sup>	[kW]	15,9	25,0	30,4	45,0	54,4
Total power input <sup>(2)</sup>	[kW]	3,97	6,34	8,15	11,7	13,8
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	4,01	3,94	3,73	3,85	3,94
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	3,41	5,39	6,63	9,77	11,70
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	47,8	54,5	56,2	34,3	47,0
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	2,73	4,31	5,24	7,75	9,36
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	23,9	27	23,1	27,9	23,3
<b>Reeferigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	1,1	1,4	1,7	2,5	3,8
Independent refrigerant circuits	[n°]	1				
Compressors type / quantity	-	Semi-hermetic pistons / 1				
Steps of capacity for each compressor (std)	-	2 (75 - 50%)	2 (75 - 50%)	2 (75 - 50%)	2 (75 - 50%)	2 (75 - 50%)
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/*S</b>						
Heating capacity <sup>(3)</sup>	[kW]	1,96	2,99	3,82	5,89	6,97
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	0,34	0,52	0,66	1,02	1,20
User circuit pressure drop <sup>(3)</sup>	[kPa]	2,6	2,4	2,3	2,6	2,4
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	6,2	10,9	12,9	16,3	20,2
Maximum absorbed current - MRA	[A]	10,8	18,9	21,6	30,2	42,0
Locked rotor current - LRA	[A]	63,1	74,6	59,1	107	125
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	1" (DN 25)	1" (DN 25)	1" (DN 25)	1" 1/2 (DN 40)	1" 1/2 (DN 40)
Evaporator side (nominal external diameter)	[inch/DN]	1" (DN 25)	1" (DN 25)	1" (DN 25)	1" 1/2 (DN 40)	1" 1/2 (DN 40)
<b>Dimensions &amp; weights (P BP/**/AS/BP/*S version)</b>						
Length	[mm]	1155	1155	1155	1155	1905
Width	[mm]	800	800	800	800	800
Height	[mm]	1420	1420	1420	1420	1420
Shipping weight	[kg]	460	470	515	535	710
Operating weight	[kg]	465	475	520	540	717
<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	69	74	74	78	78
Total sound pressure (ST version) - at 1 m distance	[db(A)]	61	66	66	70	70
Total sound pressure (ST version) - at 10 m distance	[db(A)]	41	46	46	50	50
Total sound power (LN version)	[db(A)]	67	72	72	76	76
Total sound pressure (LN version) - at 1 m distance	[db(A)]	59	64	64	68	68
Total sound pressure (LN version) - at 10 m distance	[db(A)]	39	44	44	48	48
Total sound power (SL version)	[db(A)]	65	70	70	74	74
Total sound pressure (SL version) - at 1 m distance	[db(A)]	57	62	62	66	66
Total sound pressure (SL version) - at 10 m distance	[db(A)]	37	42	42	46	46
<b>Reference conditions:</b>						

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-202

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA

## Technical data

HYDRA R290 range		65-1-1	75-1-1	90-1-1	110-1-1	90-2-2
<b>P BP/**/AS/BP/*S version</b>						
Heating capacity <sup>(1)</sup>	[kW]	80,2	90,4	106,0	126	108,0
Total power input <sup>(1)</sup>	[kW]	20,6	22,5	27,7	32,7	26,9
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,89	4,02	3,83	3,85	4,01
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	13,9	15,7	18,4	21,8	18,7
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	41,8	39,2	51,7	45,1	39,2
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	17,30	19,6	22,8	26,9	23,5
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	51,1	50,7	64,7	59,9	50,0
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	5,593	5,721	5,468	5,497	6,020
η <sub>s,h</sub>	[%]	215,7	220,9	210,7	211,9	232,8
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,397	4,422	4,306	4,323	4,734
η <sub>s,h</sub>	[%]	167,9	168,9	164,2	164,9	181,4
Cooling capacity <sup>(2)</sup>	[kW]	65,5	77,6	87	103	91,3
Total power input <sup>(2)</sup>	[kW]	17,6	19,8	23,9	28,1	23,6
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	3,72	3,92	3,64	3,67	3,87
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	14,3	16,8	19,1	22,6	19,8
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	45,7	46,2	57,3	50,1	45,0
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	11,3	13,4	15,0	17,8	15,7
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	23,7	25,5	30,4	28,3	24,3
<b>Refrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	4,3	4,5	5,8	7,1	4,2 (x2)
Independent refrigerant circuits	[n°]	1				2
Compressors type / quantity	-	Semi-hermetic pistons / 1				Semi-hermetic pistons / 2
Steps of capacity for each compressor (std)	-	2 (75 - 50%)	3 (83 - 67 - 50%)	3 (83 - 67 - 50%)	3 (83 - 67 - 50%)	2 (75 - 50%)
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/*S</b>						
Heating capacity <sup>(3)</sup>	[kW]	8,77	10,3	12,2	14,7	12,5
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	1,50	1,79	2,11	2,55	2,15
User circuit pressure drop <sup>(3)</sup>	[kPa]	2,7	2,9	2,8	3,0	4,2
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	25,2	31,8	36,6	44,2	32,6
Maximum absorbed current - MRA	[A]	42,8	53,9	61,0	74,6	60,4
Locked rotor current - LRA	[A]	145	145	159	189	137
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	1" 1/2 (DN 40)	2" (DN 50)	2" (DN 50)	2" (DN 50)	2" (DN 50)
Evaporator side (nominal external diameter)	[inch/DN]	1" 1/2 (DN 40)	1" 1/2 (DN 40)	2" (DN 50)	2" (DN 50)	2" (DN 50)
<b>Dimensions &amp; weights (P BP/**/AS/BP/*S version)</b>						
Length	[mm]	1905	1905	1905	1905	2820
Width	[mm]	800	800	800	800	1200
Height	[mm]	1420	1420	1420	1420	1640
Shipping weight	[kg]	720	750	810	845	1045
Operating weight	[kg]	727	757	817	852	1055
<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	82	82	84	84	81
Total sound pressure (ST version) - at 1 m distance	[db(A)]	74	74	76	76	73
Total sound pressure (ST version) - at 10 m distance	[db(A)]	54	54	56	56	53
Total sound power (LN version)	[db(A)]	80	80	82	82	79
Total sound pressure (LN version) - at 1 m distance	[db(A)]	72	72	74	74	71
Total sound pressure (LN version) - at 10 m distance	[db(A)]	52	52	54	54	51
Total sound power (SL version)	[db(A)]	78	78	80	80	77
Total sound pressure (SL version) - at 1 m distance	[db(A)]	70	70	72	72	69
Total sound pressure (SL version) - at 10 m distance	[db(A)]	50	50	52	52	49
<b>Reference conditions:</b>						

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA

## Technical data

HYDRA R290 range		110-2-2	130-2-2	155-2-2	190-2-2	220-2-2
<b>P BP/**/AS/BP/*S version</b>						
Heating capacity <sup>(1)</sup>	[kW]	128	161	181	215	253
Total power input <sup>(1)</sup>	[kW]	31,3	41,2	45,4	55,2	65,9
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	4,09	3,91	3,99	3,89	3,84
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	22,1	27,9	31,4	37,3	43,9
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	38,4	50,3	53,2	31,3	31,1
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	27,8	34,7	39,4	46,4	54,3
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	57,7	64,8	73,9	81,9	101,3
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	6,026	5,869	5,990	5,816	5,764
η <sub>s,h</sub>	[%]	233,1	226,7	231,6	224,7	222,6
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,779	4,649	4,737	4,580	4,554
η <sub>s,h</sub>	[%]	183,2	178,0	181,5	175,2	174,2
Cooling capacity <sup>(2)</sup>	[kW]	109	132	156	177	208
Total power input <sup>(2)</sup>	[kW]	27,3	35,2	39,9	47,6	56,2
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	3,99	3,75	3,91	3,72	3,70
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	23,5	28,7	33,6	38,7	45,5
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	44,7	55,2	62,6	34,8	34,6
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	18,8	22,7	26,5	30,5	35,8
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	28,5	30,1	36,9	38,5	47,9
<b>Refrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	5,2 (x2)	6,2 (x2)	7,3 (x2)	7,0 (x2)	8,0 (x2)
Independent refrigerant circuits	[n°]	2				
Compressors type / quantity	-	Semi-hermetic pistons / 2				
Steps of capacity for each compressor (std)	-	2 (75 - 50%)	2 (75 - 50%)	3 (83 - 67 - 50%)	3 (83 - 67 - 50%)	3 (83 - 67 - 50%)
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/*S</b>						
Heating capacity <sup>(3)</sup>	[kW]	13,4	17,1	19,2	24,2	29,9
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	2,32	2,97	3,34	4,20	5,15
User circuit pressure drop <sup>(3)</sup>	[kPa]	4,5	4,5	4,7	4,8	5,0
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	40,4	50,4	63,6	73,2	88,4
Maximum absorbed current - MRA	[A]	84,0	85,6	108	122	149
Locked rotor current - LRA	[A]	167	187	198	220	263
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	2" (DN 50)	2" (DN 50)	2" (DN 50)	3" (DN 80)	3" (DN 80)
Evaporator side (nominal external diameter)	[inch/DN]	2" (DN 50)	2" (DN 50)	2" (DN 50)	3" (DN 80)	3" (DN 80)
<b>Dimensions &amp; weights (P BP/**/AS/BP/*S version)</b>						
Length	[mm]	2820	2820	2820	2820	2820
Width	[mm]	1200	1200	1200	1200	1200
Height	[mm]	1640	1640	1640	1640	1640
Shipping weight	[kg]	1145	1180	1225	1345	1370
Operating weight	[kg]	1155	1190	1235	1355	1380
<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	81	85	85	87	87
Total sound pressure (ST version) - at 1 m distance	[db(A)]	73	77	77	79	79
Total sound pressure (ST version) - at 10 m distance	[db(A)]	53	57	57	59	59
Total sound power (LN version)	[db(A)]	79	83	83	85	85
Total sound pressure (LN version) - at 1 m distance	[db(A)]	71	75	75	77	77
Total sound pressure (LN version) - at 10 m distance	[db(A)]	51	55	55	57	57
Total sound power (SL version)	[db(A)]	77	81	81	83	83
Total sound pressure (SL version) - at 1 m distance	[db(A)]	69	73	73	75	75
Total sound pressure (SL version) - at 10 m distance	[db(A)]	49	53	53	55	55
<b>Reference conditions:</b>						

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA

## Technical data

HYDRA R290 range		15-1-1	25-1-1	35-1-1	45-1-1	55-1-1
<b>P BP/**/AS/BP/II version</b>						
Heating capacity <sup>(1)</sup>	[kW]	19,3	23,6	36,9	47,5	67,5
Total power input <sup>(1)</sup>	[kW]	5,26	5,64	9,79	12,3	17,8
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,67	4,18	3,77	3,86	3,79
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	3,34	4,09	6,39	8,23	11,70
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	44,3	31,9	50,5	24,3	44,9
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	4,07	5,20	7,86	10,20	14,40
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	49,1	37,9	47,9	45,5	50,4
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	4,955	6,187	5,720	5,675	5,416
$\eta_{s,h}$	[%]	190,2	239,5	220,8	219,0	208,6
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,061	4,766	4,346	4,327	4,237
$\eta_{s,h}$	[%]	154,4	182,6	165,9	165,1	161,5
Cooling capacity <sup>(2)</sup>	[kW]	15,7	20,7	30,7	39,5	56,0
Total power input <sup>(2)</sup>	[kW]	4,64	4,89	8,32	10,4	15,8
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	3,38	4,23	3,69	3,80	3,54
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	3,50	4,40	6,71	8,60	12,30
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	50,1	37,9	57,4	27,3	51,4
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	2,71	3,56	5,29	6,80	9,64
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	23,6	19,2	23,5	22,1	24,5
<b>Reeferant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	1,1	1,4	1,7	2,5	3,8
Independent refrigerant circuits	[n°]	1				
Compressors type / quantity	-	Semi-hermetic pistons / 1				
Type of capacity control	-	VFD				
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/II</b>						
Heating capacity <sup>(3)</sup>	[kW]	2,41	2,34	3,91	5,38	8,2
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	0,42	0,41	0,68	0,94	1,42
User circuit pressure drop <sup>(3)</sup>	[kPa]	3,8	1,6	2,4	2,2	3,3
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	5,7	6,2	10,9	12,9	16,3
Maximum absorbed current - MRA	[A]	10,7	10,8	18,9	21,6	30,2
Locked rotor current - LRA	[A]	10,7	10,8	18,9	21,6	30,2
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	1" (DN 25)	1" (DN 25)	1" (DN 25)	1" 1/2 (DN 40)	1" 1/2 (DN 40)
Evaporator side (nominal external diameter)	[inch/DN]	1" (DN 25)	1" (DN 25)	1" (DN 25)	1" 1/2 (DN 40)	1" 1/2 (DN 40)
<b>Dimensions &amp; weights (P BP/**/AS/BP/II version)</b>						
Length	[mm]	1155	1155	1155	1155	1905
Width	[mm]	800	800	800	800	800
Height	[mm]	1420	1420	1420	1420	1420
Shipping weight	[kg]	460	470	515	535	710
Operating weight	[kg]	465	475	520	540	717
<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	69	74	74	78	78
Total sound pressure (ST version) - at 1 m distance	[db(A)]	61	66	66	70	70
Total sound pressure (ST version) - at 10 m distance	[db(A)]	41	46	46	50	50
Total sound power (LN version)	[db(A)]	67	72	72	76	76
Total sound pressure (LN version) - at 1 m distance	[db(A)]	59	64	64	68	68
Total sound pressure (LN version) - at 10 m distance	[db(A)]	39	44	44	48	48
Total sound power (SL version)	[db(A)]	65	70	70	74	74
Total sound pressure (SL version) - at 1 m distance	[db(A)]	57	62	62	66	66
Total sound pressure (SL version) - at 10 m distance	[db(A)]	37	42	42	46	46
<b>Reference conditions:</b>						

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-202

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA

## Technical data

HYDRA R290 range		65-1-1	75-1-1	90-1-1	110-1-1	90-2-2
<b>P BP/**/AS/BP/II version</b>						
Heating capacity <sup>(1)</sup>	[kW]	78,9	99,3	110,0	133	95,9
Total power input <sup>(1)</sup>	[kW]	20,6	27,0	29,9	36,0	24,7
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,83	3,68	3,68	3,69	3,88
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	13,7	17,2	19,0	23,0	16,6
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	40,6	46,4	55,1	49,7	31,7
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	16,90	21,0	23,3	28,0	20,6
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	49,0	57,0	67,2	64,2	39,5
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	5,939	5,296	5,320	5,300	5,968
η <sub>s,h</sub>	[%]	229,6	203,9	204,8	204,0	230,7
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,681	4,171	4,207	4,161	4,566
η <sub>s,h</sub>	[%]	179,2	158,8	160,3	158,4	174,7
Cooling capacity <sup>(2)</sup>	[kW]	66,3	79,5	91,9	107	80,1
Total power input <sup>(2)</sup>	[kW]	18,1	23,1	26,4	31,2	20,9
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	3,66	3,44	3,48	3,43	3,83
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	14,5	17,6	20,3	23,7	17,4
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	47,0	50,7	64,4	54,7	35,8
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	11,4	13,7	15,8	18,4	13,8
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	24,3	26,6	33,5	30,0	19,2
<b>Refrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	4,3	4,5	5,8	7,1	4,2 (x2)
Independent refrigerant circuits	[n°]	1				2
Compressors type / quantity	-	Semi-hermetic pistons / 1				Semi-hermetic pistons / 2
Type of capacity control	-	VFD				
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/II</b>						
Heating capacity <sup>(3)</sup>	[kW]	8,99	12,5	13,5	16,8	11,1
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	1,55	2,16	2,34	2,89	1,93
User circuit pressure drop <sup>(3)</sup>	[kPa]	2,8	4,1	3,4	3,7	3,5
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	24,8	24,7	31,9	36,6	25,8
Maximum absorbed current - MRA	[A]	42,0	42,8	53,9	61,0	43,2
Locked rotor current - LRA	[A]	42,0	42,8	53,9	61,0	43,2
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	1" 1/2 (DN 40)	2" (DN 50)	2" (DN 50)	2" (DN 50)	2" (DN 50)
Evaporator side (nominal external diameter)	[inch/DN]	1" 1/2 (DN 40)	1" 1/2 (DN 40)	2" (DN 50)	2" (DN 50)	2" (DN 50)
<b>Dimensions &amp; weights (P BP/**/AS/BP/II version)</b>						
Length	[mm]	1905	1905	1905	1905	2820
Width	[mm]	800	800	800	800	1200
Height	[mm]	1420	1420	1420	1420	1640
Shipping weight	[kg]	720	750	810	845	1045
Operating weight	[kg]	727	757	817	852	1055
<b>Noise levels <sup>(3)</sup></b>						
Total sound power (ST version)	[db(A)]	82	82	84	84	81
Total sound pressure (ST version) - at 1 m distance	[db(A)]	74	74	76	76	73
Total sound pressure (ST version) - at 10 m distance	[db(A)]	54	54	56	56	53
Total sound power (LN version)	[db(A)]	80	80	82	82	79
Total sound pressure (LN version) - at 1 m distance	[db(A)]	72	72	74	74	71
Total sound pressure (LN version) - at 10 m distance	[db(A)]	52	52	54	54	51
Total sound power (SL version)	[db(A)]	78	78	80	80	77
Total sound pressure (SL version) - at 1 m distance	[db(A)]	70	70	72	72	69
Total sound pressure (SL version) - at 10 m distance	[db(A)]	50	50	52	52	49

#### Reference conditions:

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA

## Technical data

HYDRA R290 range		110-2-2	130-2-2	155-2-2	190-2-2	220-2-2
<b>P BP/**/AS/BP/II version</b>						
Heating capacity <sup>(1)</sup>	[kW]	135	159	199	225	267
Total power input <sup>(1)</sup>	[kW]	35,4	41,3	54,3	59,8	72,6
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,81	3,85	3,66	3,76	3,68
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	23,4	27,5	34,5	39,0	46,2
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	42,7	49,0	62,9	33,9	34,3
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	28,9	34,0	42,1	47,8	56,4
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	61,8	62,3	83,0	86,5	108,5
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	5,696	6,163	5,483	5,647	5,521
η <sub>s,h</sub>	[%]	219,8	238,5	211,3	217,9	212,9
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,466	4,898	4,362	4,462	4,358
η <sub>s,h</sub>	[%]	170,6	187,9	166,5	170,5	166,3
Cooling capacity <sup>(2)</sup>	[kW]	112	134	160	187	215
Total power input <sup>(2)</sup>	[kW]	31,2	36,2	46,5	52,5	62,4
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	3,59	3,70	3,44	3,56	3,45
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	24,7	29,2	35,4	41,3	47,8
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	48,9	56,8	68,6	39,1	37,8
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	19,3	23,0	27,5	32,3	37,0
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	29,9	30,8	38,5	42,6	50,8
<b>Reefrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	5,2 (x2)	6,2 (x2)	7,3 (x2)	7,0 (x2)	8,0 (x2)
Independent refrigerant circuits	[n°]	2				
Compressors type / quantity	-	Semi-hermetic pistons / 2				
Type of capacity control	-	VFD				
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/II</b>						
Heating capacity <sup>(3)</sup>	[kW]	15,9	17,6	23,5	26,8	33,6
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	2,77	3,06	4,08	4,66	5,81
User circuit pressure drop <sup>(3)</sup>	[kPa]	6,1	4,8	6,7	5,8	6,2
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	32,6	49,6	49,4	63,8	73,2
Maximum absorbed current - MRA	[A]	60,4	84,0	85,6	107,8	122,0
Locked rotor current - LRA	[A]	60,4	84,0	85,6	107,8	122,0
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	2" (DN 50)	2" (DN 50)	2" (DN 50)	3" (DN 80)	3" (DN 80)
Evaporator side (nominal external diameter)	[inch/DN]	2" (DN 50)	2" (DN 50)	2" (DN 50)	3" (DN 80)	3" (DN 80)
<b>Dimensions &amp; weights (P BP/**/AS/BP/II version)</b>						
Length	[mm]	2820	2820	2820	2820	2820
Width	[mm]	1200	1200	1200	1200	1200
Height	[mm]	1640	1640	1640	1640	1640
Shipping weight	[kg]	1145	1180	1225	1345	1370
Operating weight	[kg]	1155	1190	1235	1355	1380
<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	81	85	85	87	87
Total sound pressure (ST version) - at 1 m distance	[db(A)]	73	77	77	79	79
Total sound pressure (ST version) - at 10 m distance	[db(A)]	53	57	57	59	59
Total sound power (LN version)	[db(A)]	79	83	83	85	85
Total sound pressure (LN version) - at 1 m distance	[db(A)]	71	75	75	77	77
Total sound pressure (LN version) - at 10 m distance	[db(A)]	51	55	55	57	57
Total sound power (SL version)	[db(A)]	77	81	81	83	83
Total sound pressure (SL version) - at 1 m distance	[db(A)]	69	73	73	75	75
Total sound pressure (SL version) - at 10 m distance	[db(A)]	49	53	53	55	55
<b>Reference conditions:</b>						

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA HT



Refrigerant  
R290 | GWP=3



Brazed plate  
heat exchanger



Semi-hermetic  
piston compressor



Reversible  
heat pump



SCOP

30-1-1 ↔ 230-2-2

Water to water heat pumps with reciprocating compressors for comfort applications up to 75 °C



## Solution

B - Base

## Sound version

ST - Standard

LN - Low Noise

SL - Super Low Noise

## Equipment

AS - Standard equipment

DS - Desuperheater

Heating capacity 36,2 - 283 kW

Cooling capacity 30,3 - 240 kW

<b>Safety system</b>	To ensure a high level of safety throughout the useful life of the selected propane unit, special measures have been introduced that make this product unique. In fact, the refrigeration circuit is watertight and sufficiently robust, the pipes have been designed to have few joints and welds and all the materials used are compatible with the R290 refrigerant (propane). The electrical panel is installed in a separate compartment and some of the most important components are ATEX certified. In addition, the unit is equipped with a refrigerant gas leak detector and with a centrifugal suction expulsion fan, both ATEX certified.
<b>Refrigerant charge</b>	Maximum allowable charge of Refrigerating systems and heat pumps should be evaluated according to EN378:2016 that is a safety and environmental standard published by CEN that provides guidance for Design, Construction, Installation, Operation and Maintenance of Refrigerating systems and heat pumps.
<b>Structure</b>	Structure specifically designed and built to guarantee total resistance to atmospheric agents and corrosion. Basement and panels made of galvanized steel sheet, oven-painted with polyurethane powders. Frame made of anodized aluminium profiles, with aluminium alloy corner joints that guarantee excellent mechanical resistance and low weight. LN (Low Noise) version: the panels are internally lined with sound-absorbing material. SL (Super Low Noise) version: the panels are sandwich and insulated with rock wool.
<b>Compressor</b>	Reciprocating semi-hermetic type compressor equipped with: electronic control module and protection of the electric motor (installed inside the electrical panel); oil charge; oil level sight glass and oil crankcase heater; anti-vibration rubber supports; anti-vibration pipes (suction and discharge); suction and discharge valves. The compressor can be supplied with one or more RSH capacity control heads to guarantee an adaptation of the cooling capacity in case of thermal load's reduction: please see the list of accessories for further information.
<b>Water heat exchangers</b>	Brazed plate-type heat exchangers, stainless steel AISI 316 made, complete with water differential pressure switch, air vent valve and thermally insulated with closed-cell neoprene anti-condensate material. The heat exchangers design provides high thermal exchange and high performance results, furthermore it guarantees small dimensions and easy installation and maintenance.
<b>Electrical board</b>	Each unit is equipped with electric panel, built, wired and fully tested at the factory. Wiring numeration and optimized layout facilitate troubleshooting. The installed components are identified by nameplates to better identify the application and the type of action. Switchboard is made according to standards IEC 204-1/EN60204-1 and it is complete with the following main components: - Main isolator switch - Door interlock safety device - Contactor and protection for compressor and fans - Cabinet minimum protection rating IP54. To ensure higher level of security, the cabinet is outside the machine and positioned on one side of the unit. The propane sensor is equipped with separate power supply: this power supply must always be guaranteed in order to ensure the monitoring of any leakage.
<b>Control</b>	The programmable electronic microprocessor control system allows you to automatically adjust the thermal or cooling power supplied by the unit and to manage malfunction alarms. Thanks to a multitasking operating system and the adoption of standard, local and remote connectivity protocols, the selected controller is a powerful control system that can be easily interfaced with the most common Building Management Systems (BMS) on the market.
<b>Refrigerant circuit</b>	Filter drier, moisture-liquid sight glass, electronic expansion valve, high & low pressure gauge, high and low pressure transducers, high pressure switch, safety high pressure valve (when required by EN 378-2016 standard).
<b>Water circuit</b>	<b>Base version:</b> as interface to the plant, includes the water fittings of the evaporator only.

## MAIN ACCESSORIES

- Anti-vibration rubber/bell mounts
- Stainless steel panels (AISI 304)
- Double safety valve with changeover valve
- Electronic flow switch hydraulic circuit - Evaporator
- Flanges and counter-flanges for water fittings
- Hydraulic circuit pipes in stainless steel
- Water filter
- Double gas detector with separate electrical supply
- Energy meter for measuring the electric energy consumed
- Cloud GATE" device for monitoring and remote management
- UNIT COLLECT - Cascade unit management system

# HYDRA HT

## Technical data

HYDRA HT R290 range		30-1-1	40-1-1	50-1-1	70-1-1	95-1-1
<b>P BP/**/AS/BP/II version</b>						
Heating capacity <sup>(1)</sup>	[kW]	36,2	44,4	65,8	93,5	118
Total power input <sup>(1)</sup>	[kW]	10,6	12,8	18,8	27,3	34,8
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,42	3,47	3,50	3,42	3,39
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	6,26	7,68	11,4	16,2	20,5
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	45,8	43,9	53,9	72,0	58,2
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	7,44	9,20	13,7	19,4	24,4
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	85,6	90,9	107	120	110
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	5,431	5,522	5,624	5,483	5,432
η <sub>s,h</sub>	[%]	209,2	212,9	217,0	211,3	209,3
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,295	4,360	4,446	4,365	4,321
η <sub>s,h</sub>	[%]	163,8	166,4	169,9	166,6	164,8
Cooling capacity <sup>(2)</sup>	[kW]	30,3	37,7	55,5	78,2	99,1
Total power input <sup>(2)</sup>	[kW]	9,39	11,4	16,5	24,1	30,9
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	3,23	3,31	3,36	3,24	3,21
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	6,81	8,42	12,3	17,5	22,3
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	57,1	55,3	66,8	89,0	72,4
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	5,22	6,49	9,57	13,5	17,1
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	48,6	52,0	60,1	67,0	62,4

<b>Refrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	1,3	1,5	1,9	2,6	3,3
Independent refrigerant circuits	[n°]	1				
Compressors type / quantity	-	Semi-hermetic pistons / 1				
Type of capacity control	-	VFD				
Expansion valve type	-	Electronic				

<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	11,7	15,3	22,1	33,2	42,6
Maximum absorbed current - MRA	[A]	18,7	24,5	35,4	53,3	68,3
Locked rotor current - LRA	[A]	18,7	24,5	35,4	53,3	68,3

<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	1" (DN 25)	1" (DN 25)	1" 1/2 (DN 40)	1" 1/2 (DN 40)	1" 1/2 (DN 40)
Evaporator side (nominal external diameter)	[inch/DN]	1" (DN 25)	1" 1/2 (DN 40)	1" 1/2 (DN 40)	2" (DN 50)	2" (DN 50)

<b>Dimensions &amp; weights (P BP/**/AS/BP/II version)</b>						
Length	[mm]	1155	1155	1905	1905	1905
Width	[mm]	800	800	800	800	800
Height	[mm]	1420	1420	1420	1420	1420
Shipping weight	[kg]	515	535	710	750	810
Operating weight	[kg]	520	540	717	757	817

<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	74	78	78	82	84
Total sound pressure (ST version) - at 1 m distance	[db(A)]	66	70	70	74	76
Total sound pressure (ST version) - at 10 m distance	[db(A)]	46	50	50	54	56
Total sound power (LN version)	[db(A)]	72	76	76	80	82
Total sound pressure (LN version) - at 1 m distance	[db(A)]	64	68	68	72	74
Total sound pressure (LN version) - at 10 m distance	[db(A)]	44	48	48	52	54
Total sound power (SL version)	[db(A)]	70	74	74	78	80
Total sound pressure (SL version) - at 1 m distance	[db(A)]	62	66	66	70	72
Total sound pressure (SL version) - at 10 m distance	[db(A)]	42	46	46	50	52

#### Reference conditions:

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA HT

## Technical data

HYDRA HT R290 range		115-1-1	105-2-2	150-2-2	195-2-2	230-2-2
<b>P BP/**/AS/BP/II version</b>						
Heating capacity <sup>(1)</sup>	[kW]	140	132	186	238	283
Total power input <sup>(1)</sup>	[kW]	41,0	37,5	54,8	69,6	82,3
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,41	3,52	3,39	3,42	3,44
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	24,3	22,9	32,3	41,2	49,1
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	61,3	43,2	63,6	73,7	84,2
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	29,0	27,6	38,4	49,2	58,8
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	111	104	122	121	135
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	5,474	5,784	5,586	5,629	5,677
$\eta_{s,h}$	[%]	211,0	223,3	215,4	217,2	219,1
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,353	4,608	4,482	4,510	4,558
$\eta_{s,h}$	[%]	166,1	176,3	171,3	172,4	174,3
Cooling capacity <sup>(2)</sup>	[kW]	118	112	156	200	240
Total power input <sup>(2)</sup>	[kW]	36,4	33,2	48,6	61,8	73,0
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	3,24	3,37	3,21	3,24	3,29
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	26,4	24,9	35,1	44,9	53,5
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	76,3	53,8	79,1	91,9	105
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	20,3	19,3	26,9	34,5	41,2
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	62,6	59,0	68,8	68,6	76,7

<b>Refrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	4,2	5,1	5,9	9,8	12,1
Independent refrigerant circuits	[n°]	1		2		
Compressors type / quantity	-	Semi-hermetic pistons / 1		Semi-hermetic pistons / 2		
Type of capacity control	-	VFD				
Expansion valve type	-	Electronic				

<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	52,1	44,2	66,4	85,2	104
Maximum absorbed current - MRA	[A]	83,5	70,8	107	137	167
Locked rotor current - LRA	[A]	83,5	70,8	107	137	167

<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	2" (DN 50)	2" (DN 50)	3" (DN 80)	3" (DN 80)	3" (DN 80)
Evaporator side (nominal external diameter)	[inch/DN]	2" (DN 50)	2" (DN 50)	2" (DN 50)	3" (DN 80)	3" (DN 80)

<b>Dimensions &amp; weights (P BP/**/AS/BP/II version)</b>						
Length	[mm]	1905	2820	2820	2820	2820
Width	[mm]	800	1200	1200	1200	1200
Height	[mm]	1420	1640	1640	1640	1640
Shipping weight	[kg]	845	1145	1225	1345	1370
Operating weight	[kg]	852	1155	1235	1355	1380

<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	84	81	85	87	87
Total sound pressure (ST version) - at 1 m distance	[db(A)]	76	73	77	79	79
Total sound pressure (ST version) - at 10 m distance	[db(A)]	56	53	57	59	59
Total sound power (LN version)	[db(A)]	82	79	83	85	85
Total sound pressure (LN version) - at 1 m distance	[db(A)]	74	71	75	77	77
Total sound pressure (LN version) - at 10 m distance	[db(A)]	54	51	55	57	57
Total sound power (SL version)	[db(A)]	80	77	81	83	83
Total sound pressure (SL version) - at 1 m distance	[db(A)]	72	69	73	75	75
Total sound pressure (SL version) - at 10 m distance	[db(A)]	52	49	53	55	55

#### Reference conditions:

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA HT+

35-2-1 S ↔ 220-4-2 S



Refrigerant  
R290 | GWP=3



Braze plate  
heat exchanger



Scroll  
Compressor



Reversible  
heat pump



SCOP

Water to water heat pumps with scroll compressors for comfort applications up to 75 °C



## Solution

B - Base

## Sound version

ST - Standard

LN - Low Noise

SL - Super Low Noise

## Equipment

AS - Standard equipment

DS - Desuperheater

Heating capacity 39 - 244 kW

Cooling capacity 34 - 211 kW

<b>Safety system</b>	To ensure a high level of safety throughout the useful life of the selected propane unit, special measures have been introduced that make this product unique. In fact, the refrigeration circuit is watertight and sufficiently robust, the pipes have been designed to have few joints and welds and all the materials used are compatible with the R290 refrigerant (propane). The electrical panel is installed in a separate compartment and some of the most important components are ATEX certified. In addition, the unit is equipped with a refrigerant gas leak detector and with a centrifugal suction expulsion fan, both ATEX certified.
<b>Refrigerant charge</b>	Maximum allowable charge of Refrigerating systems and heat pumps should be evaluated according to EN378:2016 that is a safety and environmental standard published by CEN that provides guidance for Design, Construction, Installation, Operation and Maintenance of Refrigerating systems and heat pumps.
<b>Structure</b>	Structure specifically designed and built to guarantee total resistance to atmospheric agents and corrosion. Basement and panels made of galvanized steel sheet, oven-painted with polyurethane powders. Frame made of anodized aluminium profiles, with aluminium alloy corner joints that guarantee excellent mechanical resistance and low weight. LN (Low Noise) version: the panels are internally lined with sound-absorbing material. SL (Super Low Noise) version: the panels are sandwich and insulated with rock wool.
<b>Compressor</b>	Hermetic scroll compressor with specially designed and optimized orbiting spirals for use with the selected refrigerant. These latest generation compressors offer high energy performance. The electric motor, three-phase 2-pole, is cooled by the refrigerant gas coming from the suction side and is protected against any operating anomalies and excessive discharge temperature, with over-temperature devices and motor overcurrent and / or integral electronic protection. The compressor is fitted on rubber anti-vibration mountings in order to reduce vibrations towards the structure and facilitate installation. The compressor is supplied with dedicated lubricating oil charge for Propane and has a fully hermetic design, safe for flammable refrigerants (A3). These compressors guarantee a reduced level of sound emission, a limited inrush current and a high MTBF (Mean Time Before Failure - average time between failures). The electrical terminals of the motor are placed in a dedicated box realized with IP54 protection.
<b>Water heat exchangers</b>	Braze plate-type heat exchangers, stainless steel AISI 316 made, complete with water differential pressure switch, air vent valve and thermally insulated with closed-cell neoprene anti-condensate material. The heat exchangers design provides high thermal exchange and high performance results, furthermore it guarantees small dimensions and easy installation and maintenance.
<b>Electrical board</b>	Each unit is equipped with electric panel, built, wired and fully tested at the factory. Wiring numeration and optimized layout facilitate troubleshooting. The installed components are identified by nameplates to better identify the application and the type of action. Switchboard is made according to standards IEC 204-1/EN60204-1 and it is complete with the following main components: - Main isolator switch - Door interlock safety device - Contactor and protection for compressor and fans - Cabinet minimum protection rating IP54. To ensure higher level of security, the cabinet is outside the machine and positioned on one side of the unit. The propane sensor is equipped with separate power supply: this power supply must always be guaranteed in order to ensure the monitoring of any leakage.
<b>Control</b>	The programmable electronic microprocessor control system allows you to automatically adjust the thermal or cooling power supplied by the unit and to manage malfunction alarms. Thanks to a multitasking operating system and the adoption of standard, local and remote connectivity protocols, the selected controller is a powerful control system that can be easily interfaced with the most common Building Management Systems (BMS) on the market.
<b>Refrigerant circuit</b>	Filter drier, moisture-liquid sight glass, electronic expansion valve, high & low pressure gauge, high and low pressure transducers, high pressure switch, safety high pressure valve (when required by EN 378-2016 standard).
<b>Water circuit</b>	<b>Base version:</b> as interface to the plant, includes the water fittings of the evaporator only.

## MAIN ACCESSORIES

- Anti-vibration rubber/bell mounts
- Stainless steel panels (AISI 304)
- Double safety valve with changeover valve
- Electronic flow switch hydraulic circuit - Evaporator
- Flanges and counter-flanges for water fittings
- Hydraulic circuit pipes in stainless steel
- Water filter
- 1 VFD compressor per circuit
- Double gas detector with separate electrical supply
- Energy meter for measuring the electric energy consumed
- Cloud GATE" device for monitoring and remote management
- UNIT COLLECT - Cascade unit management system

# HYDRA HT+

## Technical data

HYDRA HT+ R290 range		35-2-1 S	40-2-1 S	45-2-1 S	65-2-1 S	85-2-1 S
<b>P BP/**/AS/BP/OO version</b>						
Heating capacity <sup>(1)</sup>	[kW]	38,9	43,7	49,1	74,0	94,4
Total power input <sup>(1)</sup>	[kW]	9,86	11,0	12,2	18,8	24,0
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,95	3,97	4,02	3,94	3,93
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	6,7	7,6	8,5	12,8	16,4
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	48,0	42,7	41,0	56,4	51,8
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	8,5	9,5	10,7	16,1	20,4
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	79,7	83,4	74,4	90,4	84,6
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	5,583	5,652	5,732	5,682	5,829
η <sub>s,h</sub>	[%]	215,3	218,1	221,3	219,3	225,2
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,438	4,480	4,528	4,511	4,535
η <sub>s,h</sub>	[%]	169,5	171,2	173,1	172,5	173,4
Cooling capacity <sup>(2)</sup>	[kW]	33,7	38,0	42,9	64,1	81,9
Total power input <sup>(2)</sup>	[kW]	8,31	9,22	10,3	15,9	19,9
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	4,06	4,12	4,17	4,03	4,12
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	7,2	8,1	9,1	13,7	17,5
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	58,3	51,9	50,0	68,4	62,7
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	5,8	6,5	7,4	11,0	14,1
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	43,8	45,7	40,9	49,5	46,9
<b>Refrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	1,1	1,2	1,5	1,9	2,9
Independent refrigerant circuits	[n°]	1				
Compressors type / quantity	-	Scroll / 2				
Capacity steps	-	0% - 50% - 100%				
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/OO</b>						
Heating capacity <sup>(3)</sup>	[kW]	3,71	4,04	4,42	7,08	9,45
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	0,65	0,70	0,77	1,22	1,64
User circuit pressure drop <sup>(3)</sup>	[kPa]	4,5	4,7	5,2	5,4	4,4
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	24,6	27,8	31,0	48,0	64,0
Maximum absorbed current - MRA	[A]	29,8	32,6	36,0	53,4	72,6
Locked rotor current - LRA	[A]	138	139	141	165	246
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	1" 1/4 (DN 32)	1" 1/4 (DN 32)	1" 1/4 (DN 32)	1" 1/2 (DN 40)	2" (DN 50)
Evaporator side (nominal external diameter)	[inch/DN]	1" 1/4 (DN 32)	1" 1/4 (DN 32)	1" 1/2 (DN 40)	2" (DN 50)	2" (DN 50)
<b>Dimensions &amp; weights (P BP/**/AS/BP/OO version)</b>						
Length	[mm]	1155	1155	1905	1905	1905
Width	[mm]	800	800	800	800	800
Height	[mm]	1420	1420	1420	1420	1420
Shipping weight	[kg]	555	565	690	690	845
Operating weight	[kg]	560	570	697	697	852
<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	75	78	79	87	88
Total sound pressure (ST version) - at 1 m distance	[db(A)]	59	62	63	71	72
Total sound pressure (ST version) - at 10 m distance	[db(A)]	44	47	47	55	56
Total sound power (LN version)	[db(A)]	73	76	77	85	86
Total sound pressure (LN version) - at 1 m distance	[db(A)]	57	60	61	69	70
Total sound pressure (LN version) - at 10 m distance	[db(A)]	42	45	45	53	54
Total sound power (SL version)	[db(A)]	71	74	75	83	84
Total sound pressure (SL version) - at 1 m distance	[db(A)]	55	58	59	67	68
Total sound pressure (SL version) - at 10 m distance	[db(A)]	40	43	43	51	52
<b>Reference conditions:</b>						

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA HT+

## Technical data

HYDRA HT+ R290 range		110-2-1 S	90-4-2 S	135-4-2 S	175-4-2 S	220-4-2 S
<b>P BP/**/AS/BP/OO version</b>						
Heating capacity <sup>(1)</sup>	[kW]	121	97,6	147	189	243
Total power input <sup>(1)</sup>	[kW]	30,9	24,8	38,0	47,8	62,2
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,92	3,94	3,87	3,95	3,91
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	21,0	16,9	25,5	32,7	42,1
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	48,9	38,1	50,6	58,3	69,9
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	26,3	21,2	31,8	41,0	52,6
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	95,0	104	105	103	121
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	5,798	5,802	5,797	6,053	5,993
η <sub>s,h</sub>	[%]	223,9	224,1	223,9	234,1	231,7
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,528	4,640	4,647	4,758	4,739
η <sub>s,h</sub>	[%]	173,1	177,6	177,9	182,3	181,6
Cooling capacity <sup>(2)</sup>	[kW]	105	84,5	127	164	211
Total power input <sup>(2)</sup>	[kW]	25,6	20,9	32,2	39,5	51,4
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	4,10	4,04	3,94	4,15	4,11
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	22,4	18,1	27,4	34,9	44,9
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	59,1	46,3	61,5	70,5	84,6
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	18,1	14,6	21,9	28,2	36,2
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	52,4	57,1	57,9	57,0	67,0
<b>Reefrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	3,8	1,6 (x2)	2,3 (x2)	3,1 (x2)	4,2 (x2)
Independent refrigerant circuits	[n°]	1,0	2			
Compressors type / quantity	-	Scroll / 2		Scroll / 4		
Capacity steps	-	0% - 50% - 100%		0% - 25% - 50% - 75% - 100%		
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/OO</b>						
Heating capacity <sup>(3)</sup>	[kW]	12,3	9,54	15,4	18,5	24,8
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	2,15	1,66	2,68	3,22	4,31
User circuit pressure drop <sup>(3)</sup>	[kPa]	3,0	7,3	7,6	6,0	4,6
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	78,0	62,0	96,0	128	156
Maximum absorbed current - MRA	[A]	96,8	72,0	107	145	194
Locked rotor current - LRA	[A]	322	177	218	319	419
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	2" (DN 50)	2" (DN 50)	2 1/2" (DN 65)	2 1/2" (DN 65)	3" (DN 80)
Evaporator side (nominal external diameter)	[inch/DN]	2 1/2" (DN 65)	2" (DN 50)	2 1/2" (DN 65)	3" (DN 80)	3" (DN 80)
<b>Dimensions &amp; weights (P BP/**/AS/BP/OO version)</b>						
Length	[mm]	1905	2820	2820	2820	2820
Width	[mm]	800	1200	1200	1200	1200
Height	[mm]	1420	1640	1640	1640	1640
Shipping weight	[kg]	865	1105	1105	1405	1410
Operating weight	[kg]	872	1115	1115	1415	1420
<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	88	82	90	91	91
Total sound pressure (ST version) - at 1 m distance	[db(A)]	72	64	72	73	73
Total sound pressure (ST version) - at 10 m distance	[db(A)]	56	50	58	59	59
Total sound power (LN version)	[db(A)]	86	80	88	89	89
Total sound pressure (LN version) - at 1 m distance	[db(A)]	70	62	70	71	71
Total sound pressure (LN version) - at 10 m distance	[db(A)]	54	48	56	57	57
Total sound power (SL version)	[db(A)]	84	78	86	87	87
Total sound pressure (SL version) - at 1 m distance	[db(A)]	68	60	68	69	69
Total sound pressure (SL version) - at 10 m distance	[db(A)]	52	46	54	55	55
<b>Reference conditions:</b>						

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA HT+

## Technical data

HYDRA HT+ R290 range		35-2-1 S	40-2-1 S	45-2-1 S	65-2-1 S	85-2-1 S
<b>P BP/**/AS/BP/OI version</b>						
Heating capacity <sup>(1)</sup>	[kW]	38,9	44,3	49,3	74,6	94,2
Total power input <sup>(1)</sup>	[kW]	9,89	11,2	12,2	19,0	24,1
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,93	3,96	4,04	3,93	3,91
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	6,7	7,7	8,5	12,9	16,3
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	48,0	43,5	41,3	57,0	51,6
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	8,4	9,6	10,8	16,2	20,4
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	79,5	84,7	74,8	91,2	84,2
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	5,991	6,031	5,997	6,000	6,191
η <sub>s,h</sub>	[%]	231,6	233,2	231,9	232,0	239,6
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,689	4,784	4,791	4,833	4,793
η <sub>s,h</sub>	[%]	179,5	183,4	183,6	185,3	183,7
Cooling capacity <sup>(2)</sup>	[kW]	33,6	38,3	43,0	64,5	81,6
Total power input <sup>(2)</sup>	[kW]	8,3	9,42	10,3	16,1	19,9
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	4,05	4,07	4,17	4,01	4,10
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	7,2	8,2	9,2	13,8	17,4
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	58,2	52,8	50,3	69,3	62,5
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	5,8	6,6	7,4	11,1	14,1
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	43,6	46,5	41,1	50,0	46,6
<b>Refrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	1,1	1,2	1,5	1,9	2,9
Independent refrigerant circuits	[n°]	1				
Compressors type / quantity	-	Scroll / 2				
Minimum capacity step	-	35,0%	31,0%	31,3%	23,2%	35,0%
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/OI</b>						
Heating capacity <sup>(3)</sup>	[kW]	3,72	4,17	4,44	7,28	9,49
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	0,65	0,72	0,77	1,26	1,65
User circuit pressure drop <sup>(3)</sup>	[kPa]	4,5	4,9	5,2	5,6	4,4
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	24,6	26,2	29,4	39,5	64,0
Maximum absorbed current - MRA	[A]	29,8	31,2	34,3	44,7	72,6
Locked rotor current - LRA	[A]	138	138	139	156	246
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	1" 1/4 (DN 32)	1" 1/4 (DN 32)	1" 1/4 (DN 32)	1" 1/2 (DN 40)	2" (DN 50)
Evaporator side (nominal external diameter)	[inch/DN]	1" 1/4 (DN 32)	1" 1/4 (DN 32)	1" 1/2 (DN 40)	2" (DN 50)	2" (DN 50)
<b>Dimensions &amp; weights (P BP/**/AS/BP/OI version)</b>						
Length	[mm]	1155	1155	1905	1905	1905
Width	[mm]	800	800	800	800	800
Height	[mm]	1420	1420	1420	1420	1420
Shipping weight	[kg]	560	570	700	700	865
Operating weight	[kg]	565	575	707	707	872
<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	75	78	79	87	88
Total sound pressure (ST version) - at 1 m distance	[db(A)]	59	62	63	71	72
Total sound pressure (ST version) - at 10 m distance	[db(A)]	44	47	47	55	56
Total sound power (LN version)	[db(A)]	73	76	77	85	86
Total sound pressure (LN version) - at 1 m distance	[db(A)]	57	60	61	69	70
Total sound pressure (LN version) - at 10 m distance	[db(A)]	42	45	45	53	54
Total sound power (SL version)	[db(A)]	71	74	75	83	84
Total sound pressure (SL version) - at 1 m distance	[db(A)]	55	58	59	67	68
Total sound pressure (SL version) - at 10 m distance	[db(A)]	40	43	43	51	52
<b>Reference conditions:</b>						

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022

# HYDRA HT+

## Technical data

HYDRA HT+ R290 range		110-2-1 S	90-4-2 S	135-4-2 S	175-4-2 S	220-4-2 S
<b>P BP/**/AS/BP/OI version</b>						
Heating capacity <sup>(1)</sup>	[kW]	122	97,9	148	188	244
Total power input <sup>(1)</sup>	[kW]	31,5	25,0	38,5	47,9	63,5
COP - Coefficient Of Performance <sup>(1)</sup>	[-]	3,87	3,92	3,84	3,92	3,84
Condenser water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	21,1	17,0	25,7	32,6	42,4
Condenser circuit pressure drop <sup>(1)</sup>	[kPa]	49,5	38,4	51,2	58,1	70,7
Evaporator water flow <sup>(1)</sup>	[m <sup>3</sup> /h]	26,3	21,2	32,0	40,9	52,8
Evaporator circuit pressure drop <sup>(1)</sup>	[kPa]	95,5	104,5	105,7	102,5	121,8
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Low Temperature - Average Climate</b>						
SCOP	[-]	6,145	5,930	5,904	6,269	6,126
η <sub>s,h</sub>	[%]	237,8	229,2	228,1	242,8	237,0
<b>Applications for seasonal efficiency for heating according to Commission Regulation (EU) No 813/2013 - Medium Temperature - Average Climate</b>						
SCOP	[-]	4,828	4,757	4,786	4,874	4,857
η <sub>s,h</sub>	[%]	185,1	182,3	183,4	187,0	186,3
Cooling capacity <sup>(2)</sup>	[kW]	105	84,8	128	164	211
Total power input <sup>(2)</sup>	[kW]	26,2	21,1	32,7	39,5	52,6
EER - Energy Efficiency Ratio <sup>(2)</sup>	[-]	4,01	4,02	3,91	4,15	4,01
Condenser water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	22,5	18,2	27,6	34,8	45,2
Condenser circuit pressure drop <sup>(2)</sup>	[kPa]	59,7	46,6	62,2	70,3	85,5
Evaporator water flow <sup>(2)</sup>	[m <sup>3</sup> /h]	18,1	14,6	22,0	28,1	36,3
Evaporator circuit pressure drop <sup>(2)</sup>	[kPa]	52,6	57,4	58,4	56,7	67,3
<b>Refrigerant circuit</b>						
Refrigerant / GWP <sub>(100Y)</sub>	-	R290 / 0,02				
Charge of refrigerant - Base unit	[kg]	3,8	1,6 (x2)	2,3 (x2)	3,1 (x2)	4,2 (x2)
Independent refrigerant circuits	[n°]	1	2			
Compressors type / quantity	-	Scroll / 2	Scroll / 4			
Minimum capacity step	-	27,1%	15,6%	11,6%	17,5%	13,6%
Expansion valve type	-	Electronic				
<b>Desuperheater (option) - A BP/**/DS/BP/OI</b>						
Heating capacity <sup>(3)</sup>	[kW]	12,9	9,61	15,8	18,6	25,9
Water flow <sup>(3)</sup>	[m <sup>3</sup> /h]	2,24	1,67	2,74	3,23	4,49
User circuit pressure drop <sup>(3)</sup>	[kPa]	3,2	7,4	7,9	6,1	4,9
<b>Electrical data</b>						
Power supply (main - gas detector)	-	400/3+N/50 - 230/1/50				
Maximum power input	[kW]	71,0	58,8	79,0	128	142
Maximum absorbed current - MRA	[A]	84,7	68,6	89,4	145	169
Locked rotor current - LRA	[A]	310	174	201	319	395
<b>Water connections</b>						
Condenser side (nominal external diameter)	[inch/DN]	2" (DN 50)	2" (DN 50)	2 1/2" (DN 65)	2 1/2" (DN 65)	3" (DN 80)
Evaporator side (nominal external diameter)	[inch/DN]	2 1/2" (DN 65)	2" (DN 50)	2 1/2" (DN 65)	3" (DN 80)	3" (DN 80)
<b>Dimensions &amp; weights (P BP/**/AS/BP/OI version)</b>						
Length	[mm]	1905	2820	2820	2820	2820
Width	[mm]	800	1200	1200	1200	1200
Height	[mm]	1420	1640	1640	1640	1640
Shipping weight	[kg]	885	1125	1125	1445	1445
Operating weight	[kg]	892	1135	1135	1455	1455
<b>Noise levels</b>						
Total sound power (ST version)	[db(A)]	88	82	90	91	91
Total sound pressure (ST version) - at 1 m distance	[db(A)]	72	64	72	73	73
Total sound pressure (ST version) - at 10 m distance	[db(A)]	56	50	58	59	59
Total sound power (LN version)	[db(A)]	86	80	88	89	89
Total sound pressure (LN version) - at 1 m distance	[db(A)]	70	62	70	71	71
Total sound pressure (LN version) - at 10 m distance	[db(A)]	54	48	56	57	57
Total sound power (SL version)	[db(A)]	84	78	86	87	87
Total sound pressure (SL version) - at 1 m distance	[db(A)]	68	60	68	69	69
Total sound pressure (SL version) - at 10 m distance	[db(A)]	52	46	54	55	55
<b>Reference conditions:</b>						

(1) Condenser fluid temperature IN/OUT = 40/45 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 10/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(2) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Results according to UNI EN 14511-2022

(3) Condenser fluid temperature IN/OUT = 30/35 °C - Condenser Fluid: water - Evaporator fluid temperature IN/OUT = 12/7 °C - Evaporator Fluid: water - Desuperheater water temperature IN/OUT = 40/45 °C - Results according to UNI EN 14511-2022